

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

Hobbs, New Mexico

April 18, 1939

Place

Date

OIL CONSERVATION COMMISSION
Santa Fe, New Mexico.

Gentlemen:

DUPLICATE

Following is a report on the work done and the results obtained under the heading noted above at the _____
 Repollo Oil Company W. C. Roach

Well No. _____ in the _____
 NW SW Company or Operator 21 205^{Lease} 37²
 of Sec. _____ T. _____ R. _____
 Euniee Lea
 Field, _____
 4/12/39

The dates of this work were as follows:

Notice of intention to do the work was (was not) submitted on Form C-102 on _____
 and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.) HOBB'S OFFICE

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED
 TD 3875' - 4/8/39- Ran 22" UB Tubing to bottom, loaded hole w/ 6 ton mud and
 pumped in 64 sacks cement on bottom, Pulled Tbg.- WOC
 4/10/39- Shot 7"OD Casing off @ 2050' and pulled. 7"OD set @ 3636, found top
 of cement plug 75' up in the 7"OD Casing before shooting off.
 4/11/39- Re-filled hole with heavy mud and set cement plug of 20 sacks in
 bottom of 9 5/8"OD Casing (1205'). WOC
 4/12/39- Shot off # 9 5/8"OD Casing @ 200' and pulled. Completed filling hole
 with heavy mud to bottom of cellar. Set cement plug w/ 5 sacks
 in bottom of cellar with piece of 4"2 Pipe extending 4' above the
 surface level as "REGULATION MARKER" and filled cellar level w/ Sur
 face

Mr. Gray

Mexia Torpedo Co.,

Witnessed by _____ Name _____ Company _____ Title _____

Subscribed and sworn to before me this _____
 18th day of April, 1939

[Signature]
 Notary Public
 2-4-42

My Commission expires _____

I hereby swear or affirm that the information given above is true and correct.

Name *L. Sumner*

Position Dist. Supt.

Representing Repollo Oil Co.

Company or Operator Hobbs, N.M.

Address _____

Remarks:

Ray Parkrough
 Name
 OIL & GAS INSPECTOR
 Title