

DUPLICATE

Budget Bureau 42-B256.2
Approval expires 12-31-62

(SUBMIT IN TRIPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED
Lesse No. 01620 A
Unit OCT 1-5-1961
OIL CONSERVATION COMMISSION
HOBBS-OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

~~SENECA~~ Staggs A-24 No. 5

Hobbs, New Mexico October 11, 19 51

Well No. 5 is located 1930 ft. from N line and 1980 ft. from E line of sec. 24

SE 1/4 Sec. 24
(1/4 Sec. and Sec. No.)

20-S
(Twp.)

37-E
(Range)

N.M.P.M.
(Meridian)

Staggs
(Field)

La
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well at the above location to a depth of approximately 3700' with rotary tools and from 3700' to a total depth of approximately 3930' with reverse circulation tools. All casing points will be cemented in accordance with approved methods of the U. S. Geological Survey and any other special requirements will be complied with.

It is proposed to use the following casing pattern: 10 3/4" casing to be set at approximately 250' and cemented with 250 sacks, cement to be circulated; 7" casing to be set at approximately 3700' and cemented with 1570 sacks, or sufficient cement to cover the salt section. If necessary, the pay will be shot with 250 qts. SNG.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box 427, Hobbs, New Mexico

By L. V. Shapiro

Title Dist. Supt.