

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
P.O. BOX 1987
HOBBS, NEW MEXICO

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. LC-031696A
2. NAME OF OPERATOR Conoco Inc		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P.O. Box 460 - Hobbs, NM 88240		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 1980' FWL - Unit Letter K		8. FARM OR LEASE NAME Semul Eumont
14. PERMIT NO. 30-025-06259		9. WELL NO. 54
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3522' GR		10. FIELD AND POOL, OR WILDCAT NMFWL Eumont Yates 7Rv.
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		11. SEC., T., R., & OR BLK. AND SURVEY OR AREA Queen
		12. COUNTY OR PARISH Lea
		13. STATE NM

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRU. Hit tight spot at 682'. Swedge out tight spot in first attempt. G-1H to 1030'. G-1H w/ 5 1/2" CIBP & 112 lbs 2 3/8" FBG. Set CIBP at 3626'. Circ hole w/ 90 bbls of 9.5 ppq mud (25 sk salt gel 1100 bbl 9 ppq brine). Spot 25 sks class "C" neat cement from 3626' to 3376' to isolate Queen. Spot 60 sks class "C" neat cement from 1319' - 739'. Pump 9.5 ppq mud down 5 1/2" csq into parted csq at 582'. Establish circ out annulus. Pump 310 sks class "C" neat down 5 1/2" csq & circ cement out 5 1/2" x 8 3/8" annulus. Left cement in 5 1/2" at surface. Rig down. Well P&A'd on 6/5/87

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

Signature for Federal or State office use

APPROVED

TITLE

ACCEPTED FOR RECORD

CONDITIONS OF APPROVAL, IF ANY:

DATE

PROCESSED
BY [Signature]
DATE [Signature]
RESTORATION IS COMPLETED.

*See Instructions on Reverse Side

AUG 13 1987

SJS

CARLSBAD, NEW MEXICO

Section 1061, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BLM - Carlsbad (6) ARCO (2) Amoco (2) Chevron (1) File

RECEIVED
AUG 17 1987
OCD
HOBBS OFFICE