

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRI
(Other instruction
verse side)

ATE
on re

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR <i>Conoco Inc.</i>	8. FARM OR LEASE NAME <i>Semur Eumont</i>
3. ADDRESS OF OPERATOR <i>P.O. Box 460 - Hobbs, NM 88240</i>	9. WELL NO. <i>No. 54</i>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <i>1980' FSL & 1980' FWL</i> <i>Unit Letter K</i>	10. FIELD AND POOL, OR WILDCAT <i>Eumont Unit 7 Biss Queen</i>
14. PERMIT NO. <i>30-025-06259</i>	15. ELEVATIONS (Show whether DF, RT, GR, etc.) <i>3522' GL SJS</i>
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <i>25-20S-37E</i>
	12. COUNTY OR PARISH <i>Lea</i>
	13. STATE <i>NM</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU. Set 5 1/2" CIBP at 3626'. Circ hole w/90 bbls of 9.5 ppq mud (25 sxs salt gel/100 bbl 9 ppq brine). Spot 25 sxs class "C" neat cement from 3626'-3376'. Spot 60 sxs class neat cement from 1319'-739'. Pump 9.5 ppq mud down 5 1/2" csq into parted csq at ± 582'. Establish circ out 5 1/2" x 8 7/8" annulus. Pump 310 sxs class "C" neat down 5 1/2" csq & circulate cement. Left cement in 5 1/2" at surface. Install P&A marker.

ACCEPTED FOR RECORD

SJS

JUN 29 1987

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED *[Signature]* DATE *6/16/87*

TITLE *Administrative Supervisor* DATE *6/16/87*

19. I, *[Signature]*, Acting Area Manager

TITLE *7-187* DATE *7-187*

20. OPERATIONS OF APPROVAL, IF ANY:

*See instructions on Reverse Side

Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BLM-Carlsbad (6) ARCO (2) Amoco (2) Chevron (1) File

E

RECEIVED

JUL 2 1987

OCB
MOBES OFFICE