

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIP
(Other: instruction
verse side)

TE
re

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Conoco Inc.	8. FARM OR LEASE NAME Semu Eumont
3. ADDRESS OF OPERATOR P.O. Box 460 - Hobbs, New Mexico 88240	9. WELL NO. 55
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSH 1980' FEA - Unit Letter J	10. FIELD AND POOL, OR WILDCAT MIRU / Eumont Gates 7 Rurs
14. PERMIT NO. 30-025-06260	15. ELEVATIONS (Show whether DF, RT, GR, etc.)
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 25-20S-37E
	12. COUNTY OR PARISH Lea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRU. Circulate w/100 bbls 10" brine. Run csq scraper to 3680'. Set CIBP at 3650'. Circulate wellbore w/90 bbls 9.5 ppg mud (25 sxs salt gel/100 bbl 9 ppg brine). Spot 25 sxs class "C" neat cement from 3650' - 3403'. POOH w/Hg. Spot 35 sxs class "C" neat cement from 1300' - 960'. POOH w/Hg. Perforate 5 1/2" csq w/4' spf at 330'. Pump down 5 1/2" csq & establish circulation out 5 1/2" x 8 7/8" annulus. Pump 150 sxs class "C" neat down 5 1/2" & circulate cement out 5 1/2" x 8 7/8" annulus. Install P&A marker well : P&A on 2/26/88.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm. J. Finney

TITLE Administrative Supervisor

DATE March 29, 1988

This space for Federal or State office use

APPROVAL OF
COMMISSIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See instructions on Reverse Side

SJS

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BLM-Carlsbad (16) ARCO (2) Amoco (2) Chevron (1) File.

RECEIVED
APR 18 1988
HOBBS OFFICE