

		X

INSTRUCTIONS
TO BE FURNISHED
TO THE APPLICANT

(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.

Form Approved

Land Office **Las Cruces**Lease No. **031696 a**Unit **Lease**

NOV 2 1962

GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL Temp xx	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

SEMU

November 1, 1962

Well No. **62** is located **1900** ft. from **xxx** **S** line and **990** ft. from **E** **xxx** line of sec. **25**NE/4 SE/4 Sec. 25
(1/4 Sec. and Sec. No.)T-208
(Twp.)R-37E
(Range)NMPM
(Meridian)Wilcat
(Field)Lea
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is **3531** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Subject well was drilled to TD 10,282 Granite. Csg pattern: 13-3/8" OD set at 350' w/350 sx, cmt circ; 9-5/8" OD set at 3722' w/800 sx, T/cmt 1900'. Cmt plugs set at 10,062-129' w/25 sx cmt, 8816-8916' w/40 sx cmt, 7008-7160' w/80 sx cmt. 5-1/2" OD liner set from 3616-7008' w/975 sx, circ out 50 sx. Drilled out to 6962'. Perf Drinkard 6848-54, 6858-64 w/2 JSPF. Treated perfs w/5000 gals 15% acid. Swbd 100% wtr after recovering 40 BLC. No oil or gas encountered in commercial quantities.

Permission is requested to temporarily abandon subject well in following manner: Set 50 sx cmt plug 5459-6870 & squeeze w/1500 psi. Load hole w/mud. All casing will be left in hole & wellhead will remain in place.

A subsequent report will be filed upon completion of above work.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Continental Oil Company**Address **Box 68****Eunice, New Mexico**

By

USGS-5 NMCCC-2 WAM File**Pan Am-Hbs-3 Calif-Hous & Mid-1 ea.****Atl-Hos-2**Title **District Superintendent**