

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 2511

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☐ GAS ☒ OTHER ☐
WELL ☐ WELL ☒

2. NAME OF OPERATOR

CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR

Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

2363' FSL & 0' FWL of Sec. 26

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

SEMUL EUMONT

9. WELL NO.

65

10. FIELD AND POOL, OR WILDCAT

EUMONT QUEEN (GAS)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 26, T20S, R37E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3508' DF

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

RAN TBG. 05 TO 2355'. RIH W/7 7/8" BIT & 4-4 1/2 DC'S ON 2 7/8" TBG, TAGGED AT 2228'. CO FROM 2228 TO 2369'. RAN IMP. BLK., FOUND DAMAGED CSG. AT 2370'. RIH TO MILL OUT TIGHT SPOT IN CSG. MILLED 2369 TO 2381'. SET CMT. RETAINER AT 2202' & SPOTTED 126 SX. CMT. TAG CMT. AT 1750'. PERF CSG 1699-1700' W/4 SHOTS. UNABLE TO PUMP DV. 8 7/8" OR 10 3/4" CSG. PERF CSG. AT 1404' W/4 SHOTS. CMTD. W/675 SX, LEFT 300' CMT. IN 8 5/8" CSG., 300' BETWEEN 8 7/8" & 10 3/4" CSG. & 40 SX. BETWEEN 10 3/4" & 20" CSG. PUMPED 20 SX. IN 8 5/8" CSG. INSTALLED DRY HOLE MARKER. WELL P&A 3-1-76. ABOVE PROCEDURE APPROVED BY USGS REP. ON LOCATION. PAD HAS BEEN RIPPED & LOCATION CLEARED.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. Butterfield

TITLE SR. ANALYST

DATE 3-15-76

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

H. B. MOROZ
1976BERNARD MOROZ
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

USGS(5) NMFI(1) E.L.E