

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 2511

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR CONTINENTAL OIL COMPANY	8. FARM OR LEASE NAME SEMU EUMONT
3. ADDRESS OF OPERATOR Box 460, HOBBS, N.M. 88240	9. WELL NO. 65
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 2363' FSL & 0' FWL OF SEC. 26	10. FIELD AND POOL, OR WILDCAT EUMONT QUEEN (GAS)
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3508' DF
	12. COUNTY OR PARISH LEA
	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHUT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Water has flooded the low pressure gas zone. The depleted condition of the reservoir precludes remedial work. It is proposed to PER by the following procedure: Run tubing open-ended to 3625'. Spot 300 sks. Class "C" cement. WOC. Calc. top cement 2725'. Pres. test csq. & squeeze if necessary. Perf 8 5/8" csq. 1690'-94' w/2 ISPF. Set plug @ 1400' & test for circ. between 8 5/8" - 10" csq to sfc. If so, cement w/sufficient cement w/dye marker to fill 8 5/8" - 10" annulus; leave 20' cement on top of retainer. If circ. not obtained, squeeze w/100 sks. Class "C" cement. Spot 25 sks. surface plug from 100' to sfc. Hook up pump truck to 10" - 20" annulus & pump 110 sks Class "C" cement. Erect dry hole marker.

18. I hereby certify that the foregoing is true and correct

SIGNER

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

H565-5, HAFU-4, File

*See Instructions on Reverse Side