MULTI-POINT BACA PRESSURE TEST FOR GAS WELLS levised 12-1-55

Pool				F	rmation	-	The state of the s	County					
					Special								
	Company												
Unit		Sec	Twp.		ig	e	Faro	haser	-1	•	•		
					igeFurchaser								
Tubing Wt. I.D. Set at Perf. To Gas Pay: From To L xG GC Ear.Press.													
Producing Thru: Casing												Dual	
							ED DATA	100001 V	ori iomb∙				
Tested	l Through	(Frove	r) (Che	oke)	(Meter)		LJ DA_A		Туре Тар	າຣຸ			
	/=	Fl	ow Data	a .			Tubing Data		Casing Data		-		
No.	(Time)	(Orli1	ce)	- 1	ļ	Temp.	Press.	Temp.	Press.	Temp.		Duration of Flow	
SI	Size	Siz	e j	osig	h _w	o _₽ .	osig	o _F .	psig	[⊃] F.		Hr.	
1.				-				<u> </u>	4	ļ	-		
2. <u> </u>		-								ļ <u>.</u>			
40										 			
<u> </u>		L											
	Coeffici	ent	-	Pre	Pagure	LOW CALC	CULATION:	S	10				
Vo.	(24-Hour) $\sqrt{h_{Wl}}$. (Flow Temp. Factor F+		Panton	Pooton		Rate of Flow Q-MCFPD @ 15.025 psia		
L. 2.								<u> </u>	- pv			ook) pala	
3,				+									
2 .													
ıs Liqı avity	uid Hydrod of Liquid	carbon F	atio_	-		SSURE CA		Speci	fic Gravi				
			(1 - e					5 5 3	fic Gravi	_b	wing :	·lula	
		- <u></u>											
P.		P_{t}^{2}	F _c Q		(F _c Q) ?	(Fc	و) [*] ا	F_2	22.22 3.128	Ca	ì	C Lur	
Pt	(psia)					(1-	€ - 5)			I	w	F _C	
•					-						-+-		
,										-			
bsolut	e Pocenti	al:				_MCFPD;	n						
DDRESS	3				· · · · · ·								
TIMESS								* 3-d					
OMDANT	7												

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871. Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q That Actual rate of flow at end of flow period at W. H. working pressure (P_w) . MCF/da. @ 15.025 psia and >00 F.
- PcI 72 hour wellhead snut-in casing (or tubing) pressure whichever is greater. psia
- PwI Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru subing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure tubing if flowing through tubing, casing if flowing through casing.) psia
- P_{f} Meter pressure, rsia.
- hwl Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.
- Note: If $P_{\mathbf{w}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{w}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.