

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
B3423

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Anerada Less Corporation	8. Farm or Lease Name State "W"
3. Address of Operator Drawer D, Monument, New Mexico 88065	9. Well No. 1
4. Location of Well UNIT LETTER H, 1230 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 30 TOWNSHIP 20S RANGE 37E NMPM.	10. Field and Pool, or Whicat Eunice Monument G/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3532' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

May 3, 1985 to May 14, 1985 - Installed BOP, picked up & ran pkr. & tbgr., established injection rate thru 6-5/8" csg. perf. fr. 3344' to 3695', trip out w/tbgr. & pkr., set Halliburton cement retainer in 6-5/8" csg. at 3275' & cement squeezed Grayburg San Andres zone thru 6-5/8" csg. perf. fr. 3344' to 3590' & fr. 3665' to 3695' w/267 sks. Class C neat cement with 194 sks. in formation & left 61 sks. inside 6-5/8" csg. & reversed out 12 sks. WOC. Drld. cement inside 6-5/8" csg. fr. 3265' to 3692' & tested cement squeeze w/500#. Held OK. Washed sand & cement fr. top of bridge plug at 3700' & drld. up bridge plug & drld. out cement inside 6-5/8" csg. to 3835' & circ. hole clean. Trip out w/tbgr., DC's & bit & closed in. Turned operation of well over to Gulf as part of Eunice Monument South Unit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E.B. Fisher TITLE Supv. Adm. Ser. DATE 5-24-85

ORIGINAL SIGNED BY JOHN SEXTON
DISTRICT SUPERVISOR

APPROVED BY _____ TITLE _____ DATE JUN - 3 1985

CONDITIONS OF APPROVAL, IF ANY: