

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION X	REPORT ON (Other)

March 1, 1954

Monument, New Mexico

(Date)

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

(Company or Operator)

State "NM"

(Lease)

Clarke Well Service

(Contractor)

Well No. 1 in the SE/ 1/4 NE/ 1/4 of Sec. 30

T. 20-S, R. 37-E, NMPM., Eunice Pool, Lea County.

The Dates of this work were as follows: February 22, 1954

Notice of intention to do the work (was) ~~XXXXX~~ submitted on Form C-102 on February 15, 1954.

(Cross out incorrect words)

and approval of the proposed plan (was) ~~XXXXX~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3835' TD, 3660' PBD - 6-5/8"OD Csg set@ 3710'. As per State Form C-102, dated 2/15/54, pulled 2-7/8"OD EUE Tbg & set Cast Iron Bridging plug @3660' W/2 sacks reg. cement on top. Tested 6-5/8"OD Csg W/2000#-OK. Perf. 6-5/8"OD Csg from 3474' to 3590' W/696 bullet shots & acidized perf W/1000 gal 15% LST Acid. 2-7/8"OD Tbg set @3493' W/perf from 3490' to 3493'. Swabbed well in - started flowing. Let well clean up & flowed 66.78 bbls oil no water in 14 hrs on 32/64" choke, T.P. 175#, Gas Vol 776,000 cu ft p/d - GOR 6778. Set Sweet Formation packer @3474' and Sand-oiled perf in 6-5/8"OD Csg from 3474' to 3590' W/10,000 gal refined oil and 10,000# sand. Flowed 40.43 bbl oil and .83 bbl BS in 24 hrs on 24/64" choke, T.P. 50#, Gas Vol 221,880 cu ft p/d, GOR 5547.

Witnessed by G.F. Blount
(Name)

Amerada Petroleum Corporation
(Company)

Farm Boss
(Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: [Signature]

Position: Foreman

Representing: Amerada Petroleum Corporation

Address: Drawer "D" - Monument, New Mexico

(Title)

(Date)