

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF <b>X</b>	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL	

Monument, New Mexico

March 3, 1937

Place

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

**Amerada Petroleum Corporation**

State "W"

Well No. **3** in the \_\_\_\_\_

Company or Operator

Lease

**SE  $\frac{1}{4}$  NW  $\frac{1}{4}$** of Sec. **30**T. **20**R. **37**

N. M. P. M.,

**Monument**

Field, \_\_\_\_\_

**Lea**

County.

The dates of this work were as follows: \_\_\_\_\_

Notice of intention to do the work was [~~was not~~] submitted on Form C-102 on **February 28, 1937**and approval of the proposed plan was [~~was not~~] obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

8-5/8" 32# 8-Thd. New Seamless casing was set in this well at 2535' and cemented by the Halliburton Method with 600 sacks.

Casing and fittings were tested with 1200# pump pressure and allowed to stand undisturbed for thirty minutes. No drop in pressure resulted so the cement was then drilled out of the casing and the same test of 1200# pump pressure was again applied and allowed to stand undisturbed for thirty minutes. No drop in pressure resulted so the drilling was then resumed.

Witnessed by **H. D. JoCoy** **Bass Drilling Co.** **Tool-pusher**  
Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

2 day of March, 1937Name J. A. StarkeyPosition Farm BossRepresenting Amerada Petroleum Corporation

Company or Operator

My commission expires Dec. 21, 1940Address Monument, New Mexico

Remarks:

Name

Title