NEV IEXICO OIL CONSERVATION CO ISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	X	OTICE OF I	NTENTION LLY TREAT	TO SHOO	OT OR
NOTICE OF INTENTION TO CHANGE PLANS		OTICE OF OTHERWI			
SOTICE OF INTENTION TO REPAIR WELL		OTICE OF I			·
SOTICE OF INTENTION TO DEEPEN WELL	 				-
Monument, N	New Mexic	0		Marc	h 16, 1937
IL CONSERVATION COMMISSION, anta Fe, New Mexico. entlemen: ollowing is a notice of intention to do cortain work of					Date
ollowing is a notice of intention to do certain work a Amerada Petroleum Corporation					_
Company or Operator	Leas	r)			in SW4 NW4
Sec. 30 , T. 20 , R. 37	,N. M.	P. M	Monumer	<u>nt</u>	F
County.					
THE MALLEST ON MACHINE WITH WO SHOKS	•				
8-5/8" 32# 8-Thd. New Seatless casing the Halliburton Method with 600 sacks Casing and fittings will be tested with undisturbed for thirty minutes. If no be drilled out of the casing and the sand allowed to stand undisturbed for the drilling will then be resumed.	th 1200 _{ff} o drop in	pump pre	ssure and result	d allo	owed to stand cement will
Casing and fittings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the and allowed to stand undisturbed for the drilling will then be resumed.	th 1200 m o drop in same test	pump pre	ssure an e result pump p If no dr	d allos the ressurop in	owed to stand cement will re again appl pressure res
Casing and fittings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the and allowed to stand undisturbed for the drilling will then be resumed.	th 1200 m o drop in same test	pressur of 1200 nutes.	ssure and result pump pump pump pump pump pump pump pum	d allos the ressurop in Corp	owed to stand cement will re again appl pressure res
Casing and fittings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the and allowed to stand undisturbed for the drilling will then be resumed. proved	th 1200 m o drop in same test thirty mi	pressur of 1200 nutes.	saure and result in pump pump pump pump pump pump pump pum	d allos the ressur op in Operato	owed to stand cement will re again appl pressure res
Casing and fittings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the and allowed to stand undisturbed for the drilling will then be resulted. Our conservation commission,	th 1200 m o drop in same test thirty mi	mera a	saure and result in pump properties of the company	d allos the ressur op in Operato	owed to stand cement will re again appl pressure res
Casing and fittings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the and allowed to stand undisturbed for the drilling will then be resulted. Opproved	th 1200 m o drop in same test thirty mi	pressur of 1200 nutes.	saure and result in pump properties of the company	d allos the ressur op in Operato	owed to stand cement will re again appl pressure res