

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-025-06298

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Eunice Monument
South Unit

8. Well No. 137

9. Pool name or Wildcat Eunice
Monument Grayburg SA

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Chevron USA, Inc.

3. Address of Operator

15 Smith Rd., Midland, Texas 79705

4. Well Location

Unit Letter D : 660 feet from the North line and 660 feet from the West line

Section 31

Township 20S

Range 37E

NMPM

Lea

County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Notify OCD 24 hrs prior to MI & RU.
2. Set 5 1/2" CIBP @ 3700' cap w/35' Cmt (Grayburg-San Andres) WOC Tag.
3. Displace hole w/MLF, 9.5# Brine w/25# gel P/BBL.
4. Spot 25 Sx plug 3400'-3200' (Queen)
5. Perf 4 holes @ 2500', Sqz 50 Sx plug 2500'-2300' (B-Salt) WOC Tag.
6. Cut 5 1/2" Csg @ 1250', L/D Csg.
7. Spot 50 Sx plug 1300'-1100' (7 5/8" Shoe, T-Salt) WOC Tag.
8. Perf 4 holes @ 200', Sqz 100 Sx (7 5/8" X 10 3/4" Shoe) To Surf. WOC Tag.
9. Install dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE G.R. Bledsoe

TITLE HES Specialist

DATE 5/31/2002

Type or print name G.R. Bledsoe

915

Telephone No. 687.7153

(This space for State use) SIGNED BY

GARY W. WINK

APPROVED BY FIELD REPRESENTATIVE II/STAFF MANAGER

Conditions of approval, if any:

DATE 6/10/2002

WORKSHEET

OPERATOR CHEVRON USA INC.
 LEASE NAME EUNICE MONUMENT SOUTH UNIT
 WELL # 137

SECT 31 TWN 20-S RNG 37-E
 FROM 660 NISL 660 E/WL 660
 TD 3935 FORMATION @ TD SAN ANDRES
 PBTD FORMATION @ PBTD GRAYBURG

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	10 3/4	117	SURF	Circ
INTMED 1	7 5/8	1185	SURF	Circ
INTMED 2				
PROD	5 1/2	3738	2631	CALC

	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					

	CUT & PULL	TOP - BOTTOM
INTMED 1	PERFS	
INTMED 2		
PROD	1250	3738 - 3935

*REQUIRED PLUGS DISTRICT

	PLUG	TYPE PLUG	SACKS CEMENT	DEPTH
RUSTLER (ANHYD)				
YATES	1	CIBP		3700
QUEEN	2	QUEEN	25	3400
GRAYBURG	3	B-SALT	50	2500
SAN ANDRES	4	T-SALT	50	1300
	5	SURF	100	200
CAPITAN REEF				
DELAWARE				
BELL CANYON				
CHERRY CANYON				
BRUSHY CANYON				
BONE SPRING				
GLORIETA				
BLINBRY				
TUBB				
DRINKARD				
ABO				
WC				
PENN				
STRAWN				
ATOKA				
MORROW				
MISS				
DEVONIAN				

10 3/4
 @ 117
 TOC SURF

7 5/8
 @ 1185
 TOC SURF

CIBP w/ 35' CMT
 5 1/2
 @ 3738
 TOC 2631

TD 3935