

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBES OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION Plug back & (OTHER) <b>recomplete as</b> <b>X</b>		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

**Hobbs, New Mexico**  
(Place)

**March 31, 1954**  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the **Humble-State Aggies**

**Humble Oil & Refining Company**  
(Company or Operator)

Well No. **4** in **G** (Unit)

**SE**  $\frac{1}{4}$  **NW**  $\frac{1}{4}$  of Sec. **31**, T. **20-S**, R. **37E**, NMPM., **Eunice** Pool

**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Objective: The purpose of this workover is to plug off the present producing section in the Grayburg and San Andres and recomplete as a gas well from the Yates, Seven Rivers and Queen.

- Intended Procedure:
1. Rig up unit and pull rods and tubing.
  2. Run Baker Model "K" bridge plug and set at 3700 feet.
  3. Spot 50 foot cement plug on top of bridge plug with dump bailer.
  4. Load hole with water and test casing for leaks.
  5. Perforate casing from 3300 to 3335 and from 3345 to 3420 with 2 jet shots per foot.
  6. Run tubing with hookwall packer.
  7. Circulate out salt water with oil.
  8. Set packer and swab well in.
  9. Treat perforated section as necessary.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By *[Signature]*

Title.....

mcb/mcb

**Humble Oil & Refining Company**  
Company or Operator

By *[Signature]*

Position **District Superintendent**  
Send Communications regarding well to:

Name **Humble Oil & Refining Company**

Address **Box 2347, Hobbs, N. M.**