٠,

.

									opring p	00	Form C-1:	
				MULT	I-POINT I	r . F .		er Fol :	9 WEILIS	Marine 1	Revised 12-1-5	
Pool	Eumont				Formatic	Queen	್ರಾಯಕ್ಸಿ 🔿 ನಿರ್ದೇಶಕರ್ತು	t the first of the second s	Coasty_	27		
											-21-56	
											24	
											pe Line Co.	
											494	
											255	
ate	cing Thru: of Complet	ion: '	 12-2	3_55	Packe		Si	ngle-Brad	lenhead-G.	G. or (.O. Dual	
								neserv	orr lemp.			
	= 2.08%					OBSERV	ED DATA					
	d Through) <u>(Meter</u>)	-			Type Tap		pe	
	(Prever)	(Gho	low D	Press	Diff.	Temp.	Tubing Press	z Data Temp.	Casing I Press.		Duration	
0.	(Line) Size	(Orif Si	ice) ze	psig	h _w	° _F .	osig	° _F .			of Flow Hr.	
I L			·				963.5		961.6		67 3/4	
	4	2.0		474	9 17.4	8 3 61	879.1	1	901.7	<u> </u>	24	
<u> </u>		2.0		474	29.8	63	709.1		\$22.5		24	
e •						65	604.5		783.5		24	
						FLOW CAL						
>.	Coefficie				essure	Flor Fac		Gravity Factor	Compre Facto	f	Rate of Flow Q-MCFPD	
	(24-Hour)		Y 19 1		150	P.		Fg	Fpv		@ 15.025 psia	
	29.92		61.69 91.78		488.0 .978 484.1 .999		6 .9498 0 .9498		1.039		<u>1,782</u> 2,725	
_	29.92		120.		87.5	.997		9498	1.04	6	3,571	
								.9498	1.04	•	4,277	
						ESSURE ()	AD. HATT	CHS				
vity	uid Hydrod of Liquid	l Hydro	carbo	States of States		ct/bo . de⊬.		Speca Speca	fic Gravi	ty Sepa:	rator Gas ing Fluid	
	-	- 	(-e ^{-s})		-		¹ ° 9	76.7	_P ² 95	3.9	
T P	w						*					
•		P_t^2	F	Q	$(\mathbb{F}_{nQ})^{2}$		<u>à</u> ,	₽ _w 2	$P_c^2 - P_w^2$	Cal	Pw	
	t (psia)		-		1. 1. – – – – – – – – – – – – – – – – –		ία ~ε) 	837.0	116.9	P _v	Pw Pc	
-8	76.2				n an			767.7	186.2			
7	96.7				n (n 24 - Harrison and Paramateria		1	698.4	255.5	+		
								•;**/	34.70%	1	• • • • •	
solu MPAN	te Porenti Y		11,			_MCFPE;	n	8				
DRES	S				OMPANY_ IDLAND,	TRY A Q					<u></u>	
	and TITLE	<u>L.</u>	I. 1	AKER	, DISTR	ICT GAS	MAN	~	1	Enter State		
I'NES.		- WAT	782 1	BRONN						. –••	 	

This is a retest.

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q _ Actual rate of flow at end of flow period at W. H. working pressure (P_W). MCF/da. @ 15.025 psia and 60° F.
- PcI 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- P_w Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

Pf Meter pressure, psia.

hwI Differential méter pressure, inches water.

FgI Gravity correction factor.

° (*	<i>.</i> *	*	×	*	đ
F+ T: Flowing	temperature	correction factor.	×	*	л	л
- U U	1	e	4	×	*	*
FpvI Superco	ompre ssa bili	ty factor.	а	` #	*	t

n _ Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .