


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY



SUNDRY NOTICES AND REPORTS ON WELLS

|                                                     |                                     |                                                 |  |
|-----------------------------------------------------|-------------------------------------|-------------------------------------------------|--|
| NOTICE OF INTENTION TO DRILL.....                   | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |  |
| NOTICE OF INTENTION TO CHANGE PLANS.....            |                                     | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |  |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     |                                     | SUBSEQUENT REPORT OF ALTERING CASING.....       |  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... |                                     | SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....  |  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        |                                     | SUBSEQUENT REPORT OF ABANDONMENT.....           |  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    |                                     | SUPPLEMENTARY WELL HISTORY.....                 |  |
| NOTICE OF INTENTION TO ABANDON WELL.....            |                                     |                                                 |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

A. H. Lockhart A-27 No. 3-E

Hobbs, New Mexico

September 18, 1950

Well No. 3-E is located 330 ft. from N line and 1650 ft. from EX line of sec. 27  
N 1/4 Sec. 27 21 South 37 East 11TH  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Brunson Lea New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a total depth of approximately 7725'. All casing points will be cemented in accordance with approved methods of the U.S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing pattern: 10 3/4" casing to be set at approximately 230' and cemented with 250 sacks; cement to be circulated. 7 5/8" casing to be set at approximately 2750' and cemented with approximately 1165 sacks or sufficient cement to protect the salt section as determined by temperature survey. 5 1/2" casing to be set at approximately 7725' and cemented with approximately 440 sacks as determined by temperature survey. 5 1/2" casing to be perforated opposite pay zone.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box C.

Hobbs, New Mexico

By A. H. Lockhart

Title District Superintendent

