

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

LC 032096(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

NMFU

8. FARM OR LEASE NAME

LOCKHART A-27

9. WELL NO.

8

10. FIELD AND POOL, OR WILDCAT

DRINKARD &amp; BLINNEY GR.

11. SEC., T., R., M., OR BLM. AND  
SURVEY OR AREA

SEC. 27 T-215 R-37E

12. COUNTY OR PARISH

13. STATE

LEA

N.M.

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR

Box 460, HOBBS, N.M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

810' FNL &amp; 660' FNL OF SEC. 27 OCT 8 1974

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, AT, HOBS, NEW MEXICO

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETS

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well-  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

The Lower Drinkard (Oil) Pkts were closed off by setting a  
CIBP @ 6510' w/ 1 sack cement on top. Perf w/ 4 JSPE @ 6436'-  
60', 6468'-76' & 6484'-88'. Set pkr. @ 6374' & Trtd. w/ 2000  
gals 28% NE Acid. Pulled pkr. & perf w/ 4 JSPE 6380'-83', 6397-6400',  
6410'-14', 6417'-20' & 6428'-31'. Set BP @ 6445 spot acid over parts  
Set pkr. @ 6315' & Acidize w/ 2200 gals 28%. Re-set BP @ 6500'  
& Pkr. @ 6320'. Tested both zones. Work started 5-20-74,  
completed 6-2-74.

This is still a Re-Drill Drilling

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

SR. ANALYST

DATE

10-2-74

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT 11 1974

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

USGS-\$, NMFU-4, File

\*See Instructions on Reverse Side