

DUPLICATE

(SUBMIT IN TRIPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office See 2-27
Lease No. See 2-27
Unit See 2-27
RECEIVED
JAN - 3 1951
OIL CONSERVATION COMMISSION
HOBBS OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

A. M. Lockhart A-27 No. 3

Hobbs, New Mexico December 29, 1950

Well No. 3 is located 660 ft. from N line and 1650 ft. from W line of sec. 27

27 (4 Sec. and Sec. No.) 27 (Twp.) 10N (Range) 10E (Meridian)
Hobbs (Field) Lea (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3436 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 7 5/8" casing at 2879' and cemented with 1250 sacks cement. Plug down at 12000 midnight 12-29-50. Top cement behind casing 750' by temperature survey.

On 12-29-50, after 48 hours W.O.C., pressure tested casing with 1200' for 30 minutes. Final pressure 2170'. Found top of cement plug at 2145'. Drilled out plug and tested casing with 1200' for 30 minutes. Final pressure 1144'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box 60

Hobbs, New Mexico

By E. L. Shaffer

Title District Superintendent

