




(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces

Lease No. 093096 (a)

Unit S. J. F. S.



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

A. M. Lockhart A-27 No. 6

Hobbs, New Mexico

December 7, 1950

Well No. 6 is located 660 ft. from N line and 1400 ft. from E line of sec. 27

N. 1/4 Sec. 27  
(1/4 Sec. and Sec. No.)

T1 S  
(Twp.)

R7 E  
(Range)

W 10 N  
(Meridian)

DeSoto  
(Field)

Las  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a depth of approximately 6440'. All casing points will be cemented in accordance with approved methods of the U.S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing pattern: 10 3/4" casing to be set at approximately 100' and cemented with 250 sacks. Cement to be circulated to surface. 7 7/8" casing to be set at approximately 1725' and cemented with approximately 215 sacks; cement or sufficient cement to protect the salt section as determined by Saliper Survey. 5 1/2" casing to be set at approximately 6440 and cemented with approximately 430 sacks cement as determined by Saliper Survey. 5 1/2" casing to be perforated opposite the pay zone. Approval to produce this well upon completion is also requested. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box 66


Hobbs, New Mexico

By

E. L. Shaffer

Title Asst. District Superintendent

000000 000  
(=) 000000  
0.4.0.0



00 000000 000000 000000 000000 000000  
000000 000000 000000 000000 000000 000000  
000000 000000 000000 000000 000000 000000  
000000 000000 000000 000000 000000 000000

It is our intention to publish a list of names of persons who are  
of the nature of a list of names of persons who are  
of the nature of a list of names of persons who are  
of the nature of a list of names of persons who are

It is our intention to publish a list of names of persons who are  
of the nature of a list of names of persons who are  
of the nature of a list of names of persons who are  
of the nature of a list of names of persons who are

000000 000000 000000

00 000

000000 000000 000000

000000 000000 000000