

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	<b>X</b>	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) <b>to Recomplete</b>	<b>X</b>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)November 25, 1959  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

**Gulf Oil Corporation** **J. N. Carson (NCT-A)** Well No. **5** in **J**  
(Company or Operator) (Unit)  
**NW**  $\frac{1}{4}$  **SE**  $\frac{1}{4}$  of Sec. **28**, T. **21-S**, R. **37-E**, NMPM., **Brunson** Pool  
(40-acre Subdivision)  
**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

**Subject well is uneconomical to produce. It is proposed to abandon Brunson oil zone and recomplete in the Wanta Abo as follows:**

1. Set CI bridge plug at approximately 7350'. Dump 2 sacks cement on BP.
2. Pressure test casing with 1000 psi. If O.K., run GR tie-in log with collar locator from 7350-7000'. Perforate approximate intervals 7092-7120', 7148-52', 7165-72', 7182-85', 7215-23', 7229-33', 7246-49' & 7273-80'.
3. Treat above perfs with 6000 gals 15% NE Fe acid. Swab and test.

TD 7910'. 7" csg at 7782'.

Approved..... 19.....  
Except as follows:Approved  
OIL CONSERVATION COMMISSIONBy.....  
Title.....**Gulf Oil Corporation**  
Company or OperatorBy.....  
Position..... **Area Production Supt.**  
Send Communications regarding well to:Name..... **Gulf Oil Corporation**  
Address..... **Box 2167, Hobbs, New Mexico**