

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
JAN 29 1948
HOBBBS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	7"	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

January 23, 1948 Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Gulf Oil Corporation

Carson "A"

Well No. 5 in the

Company or Operator

Lease

NW SE

of Sec. 28

T. 21S

R. 37E

, N. M. P. M.,

Brunson

Field,

Lea

County.

The dates of this work were as follows: Cemented January 20, 1948; tested January 22, 1948.

Notice of intention to do the work was ~~(was not)~~ submitted on Form C-102 on January 21, 1948

and approval of the proposed plan was ~~(was not)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On the State Form C-102 submitted January 21, 1948 - which refers to setting 7" casing - 9-5/8" was placed opposite "Notice ~~to~~ of Intention to Test Casing Shut-off". 7" should have been placed there instead of 9-5/8".

The hole was washed down and the casing tested with 1200# pressure applied for 30 minutes. The plug was drilled and the casing tested with 1200# pressure applied for 30 minutes. Both tests were OK, and after approval of Mr. Yarbrough, State Oil and Gas Inspector, preparations were made to complete well.

Top of cement back of 7" casing at 2890' per temperature survey.

Witnessed by Glenn Stach Gulf Oil Corporation Drilling Foreman
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

23rd day of January, 1948

Name E. J. Gallagher

Position District Sup't.

Representing Gulf Oil Corporation
Company or Operator

My commission expires 10-24-49

Address Box 1667, Hobbs, New Mexico

Remarks:

Roy Yarbrough
Name
Title