

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

| | | | | | |
|---|--|--|----------|---|--|
| NOTICE OF INTENTION TO CHANGE PLANS | | NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL | | NOTICE OF INTENTION TO DRILL DEEPER | |
| NOTICE OF INTENTION TO PLUG WELL | | NOTICE OF INTENTION TO PLUG BACK | | NOTICE OF INTENTION TO SET LINER | |
| NOTICE OF INTENTION TO SQUEEZE | | NOTICE OF INTENTION TO ACIDIZE | | NOTICE OF INTENTION TO SHOOT (Nitro) | |
| NOTICE OF INTENTION TO GUN PERFORATE | | NOTICE OF INTENTION (OTHER) <u>Sandlock Treat</u> | <u>X</u> | NOTICE OF INTENTION (OTHER) | |

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

March 17, 1959
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation J. N. Carson (NCT-A) Well No. 11 in K
(Company or Operator) (Unit)
NE 1/4 SW 1/4 of Sec. 28, T. 21-S, R. 37-E NMPM., Hare Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

In an effort to control sanding up of pump, it is proposed to Sandlock treat as follows:

1. Pull rods, pump and tubing.
2. Clean out to TD. Run Caliper survey.
3. Run 2-7/8" tubing & 7" Baker full bore packer. Packer set in blank interval 7650-7694'.
4. Treat open hole formation 7694-7825' with approximately 5670# plastic coated walnut shells in weak acid solution.
5. Raise tubing and packer. Set packer at approximately 40' above upper perforations (perforated interval 7494-7650').
6. Treat perforations with approximately 6330# plastic coated walnut shells.
7. Swab and test.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Gulf Oil Corporation
Company or Operator

By.....

Position.....
Send Communications regarding well to:

Name.....
Address.....