
OIL CONSERVATION COMMISSION MISCELLANEOUS REPURTS ON WELLS



Sumbit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission. Indicate nature of report by checking below. REPORT ON BEGINNING DRILLING OPERA-REPORT ON REPAIRING WELL TIONS REPORT ON RESULT OF SHOOTING OR CHEM-REPORT ON PULLING OR OTHERWISE ICAL TREATMENT OF WELL ALTERING CASING REPORT ON RESULT OF TEST OF CASING REPORT ON DEEPENING WELL SHUT-OFF 9 5-84 REPORT ON RESULT OF PLUGGING OF WELL February 21, 1947 Hobbs. N. M. Date Place OIL CONSERVATION COMMISSION. SANTA FE, NEW MEXICO. Gentlemen: Following is a report on the work done and the results obtained under the heading noted above at the____ Gulf Cil Corporation Carson *A* ____Well No.______ in the Company or Operator KE SW _, T. **21 S** , R. **27 R** , N. M. P. M., __of Sec._ Drinkard Cemented Feb 18; tested Feb. 20, 1947 The dates of this work were as follows: Notice of intention to do the work was had submitted on Form C-102 on Feb. 19. 19 47 and approval of the proposed plan was () obtained. (Cross out incorrect words.) DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED The hole was washed down and the casing tested with 1200# pressure applied for 30 minutes. The plug was drilled and the hole tested with 1200# pressure applied for 50 minutes. Both tests were OK, and after approval of Mr. Yarbrough, State Oil and Gas Inspector, preparations were made to drill shead. Temperature survey showed top of cement behind 9-5/8" casing at 1265' from surface. Gulf Oil Corporation Witnessed by Glenn Stach Name Company I hereby swear or affirm that the information given above Subscribed and sworn before me this_ is true and correct. Name _, 19_47 Position District Sun't Notary Public Representing Gulf Oil Corporation Company or Operator 10-24-49 My commission expires___ Address ___ Hobbs, New Mexico.

Remarks:

Date FEB 25 1947

Roy yarbrough