

## XICO OIL CONSERVATION CC TISSION

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be

			DOODS , M GM	Mexi co	Fe	bruary 5, 194
OIL COME	ERVATION C			lace		Date
Santa Fe, N	New Mexico,	ommission,				
Gentlemen:						
Y	ou are hereby	notified that it is ou	r intention to co	mmence the dril	ling of a well to be	known as
Gulf 01		ypsy Div.	Carso	n "A"	Well No. 2	in NE SW
e 0	_	ny or Operator		Lease		1
or Sec	N	21.5 <sub>R</sub> 37.6	, N. M., P. M., 2086	Drinkard	Field,	Count
	N				e South line	
					tion 28	
		(Give 1 directions.)	ocation from sec	tion or other leg	gal subdivision line	s. Cross out wron
		If state land	the oil and gas	lease is No	Assignmen	nt No
0		If patented	land the owner	is <b>Vm. Tu</b>	rner	
		Address		Suni ce	New Mexico	
		If governme	nt land the perr	nittee is		
		Address				·
		The lessee is	Gulf 011	Corp., Gyps	Division	
AREA	640 ACRES	Address	DOT OOT'	Tursa 2, OK	ah oma	
LOCATE WI	ELL CORRECTI	We propose t	to drill well with	drilling equipmen	it as follows:	
	to use the fell	lowing strings of casi	ing and to land o	r cement them a	s indicated:	
Size of	Size of	Weight Per Foot	New or	Denth	Landed or	Sacks
Size of Hole	Size of Casing	Weight Per Foot		Depth	Cemented	Sacks Cement
Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	3001	Cemented	Cement 300 Sx.
Size of Hole	Size of Casing 13-3/8*019-5/8* Ci	Weight Per Foot  48 36	New or Second Hand New New	300† 3000†	Cemented Cemented Cemented	300 Sx. 1800 Sx.
Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	3001	Cemented	Cement 300 Sx.
Size of Hole 17" 12-1/4"	Size of Casing 13-3/8*019-5/8* Ci	Weight Per Foot  48 36	New or Second Hand New New	300† 3000†	Cemented Cemented Cemented	300 Sx. 1800 Sx.
Size of Hole  17" 12-1/4" 8-3/4"	Size of Casing  13-3/8*0 9-5/8* 0 7* 0D	Weight Per Foot  48 36 23	New or Second Hand New New New	300° 3000° 6500°	Cemented Cemented Cemented Cemented	300 Sx. 1300 Sx. 700 Sx.
Size of Hole  17" 12-1/4" 8-3/4"  If changes in the first pro-	Size of Casing  13-3/8*0 9-5/8* Of 7* OD  The the above playeductive oil or	Weight Per Foot  48 36 23	New or Second Hand New New New	300° 3000° 6500°	Cemented Cemented Cemented Cemented	300 Sx. 1300 Sx. 700 Sx.
Size of Hole  17" 12-1/4" 8-3/4"  f changes in the first pro-	Size of Casing  13-3/8*0 9-5/8* Of 7* OD  The the above playeductive oil or	Weight Per Foot  48 36 23	New or Second Hand New New New	300° 3000° 6500°	Cemented Cemented Cemented Cemented	300 Sx. 1300 Sx. 700 Sx.
Size of Hole  17" 12-1/4" 8-3/4"  f changes in the first pro-	Size of Casing  13-3/8* OF CASING OF	Weight Per Foot  48 36 23	New or Second Hand New New New	300° 3000° 6500°	Cemented Cemented Cemented Cemented	300 Sx. 1300 Sx. 700 Sx.
Size of Hole  17"  12-1/4"  8-3/4"  f changes in the first produced th	Size of Casing  13-3/8* OF CASING OF	Weight Per Foot  48 36 23  In become advisable gas sand should occ	New or Second Hand  New New New New we will notify you car a depth o	300° 3000° 6500°	Cemented Cemented Cemented Cemented	300 Sx. 1800 Sx. 700 Sx.
Size of Hole  17" 12-1/4" 8-3/4"  f changes in the first productional in approved	Size of Casing  13-3/8* OF CASING OF	Weight Per Foot  48  36 23  In become advisable gas sand should occ	New or Second Hand  New New New New we will notify you at a depth of Since	300° 3000° 6500°  a before cementif about 5000°	Cemented Cemented Cemented Cemented  ng or landing casing feet.	300 Sx. 1800 Sx. 700 Sx.
Size of Hole  17" 12-1/4" 8-3/4"  f changes in the first productional in approved	Size of Casing  13-3/8*C  9-5/8* C  7* OD  The above play oductive oil or information:	Weight Per Foot  48  36 23  In become advisable gas sand should occ	New or Second Hand  New New New New we will notify you at a depth of Since	300° 3000° 6500°  u before cementif about 5006 erely yours, ulf Oil Corr	Cemented Cemented Cemented Cemented	300 Sx. 1800 Sx. 700 Sx.
Size of Hole  17" 12-1/4" 8-3/4"  f changes in the first productional in approved	Size of Casing  13-3/8*C  9-5/8* C  7* OD  The above play oductive oil or information:	Weight Per Foot  48  36 23  In become advisable gas sand should occ	New or Second Hand  New New New New we will notify you at a depth of Since	300° 3000° 6500°  u before cementif about 5006 erely yours, ulf Oil Corr	Cemented Cemented Cemented Cemented ong or landing casing feet.	300 Sx. 1300 Sx. 700 Sx.
Size of Hole  17" 12-1/4" 8-3/4"  f changes in the first productional in approved	Size of Casing  13-3/8*C  9-5/8* C  7* OD  The above play oductive oil or information:	Weight Per Foot  48  36 23  In become advisable gas sand should occ	New or Second Hand  New New New New Since Since G	300' 3000' 6500'  a before cementi f about 5.506  erely yours, ulf 0il Corr	Cemented Comented Comented Comented  Ing or landing casing feet.  Cypsy Divious pany or Operator Callagher	300 Sx. 1800 Sx. 700 Sx. 700 Sx.
Size of Hole  17" 12-1/4" 8-3/4"  f changes in he first productional in Approved	Size of Casing  13-3/8*0  9-5/8* Of 7* OD  The the above playeductive oil or information:	Weight Per Foot  48  36 23  In become advisable gas sand should occ	New or Second Hand  New New New New Since Second Hand  New New Second Hand  New New Second Hand  New New Second Hand  New New Second Hand  Posit	300' 3000' 6500'  a before cementife about 5.506  brely yours,  ulf 0il Correction  b. J.	Cemented Cemented Cemented Cemented ong or landing casing feet.	300 Sx. 1800 Sx. 700 Sx.
Size of Hole  17" 12-1/4" 8-3/4"  If changes in the first productional in the Approved	Size of Casing  13-3/8*0  9-5/8* Of 7* OD  The the above playeductive oil or information:	Weight Per Foot  36 23  In become advisable gas sand should occ  B   0   13   13   13   13   13   13   13	New or Second Hand  New New New New Since Second Hand  New New Second Hand  New New Second Hand  New	300' 3000' 6500'  a before cementife about 5.506  brely yours,  ulf 0il Correction  b. J.	Cemented Cemented Cemented Cemented Cemented  ong or landing casing feet.  Cypsy Divi company or Operator Callagher Superintende regarding well to	300 Sx. 1800 Sx. 700 Sx.