

OIL CONSERVATION COMMISSION





Sumbit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on reginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature	e of report by checking below.		
REPORT ON BEGINNING DRILLING OPERA- TIONS	REPORT ON REP	AIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PUL ALTERING	LING OR OTHERWISE	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEE	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			
Septer	mber 21, 1948	Hobbs, New Mer	dee
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen:	Date	Place	,
Following is a report on the work done and the resu The Obio Oil Company	ults obtained under the heading	noted above at the	· · · · · · · · · · · · · · · · · · ·
Company or Operator	Lease		
SE/4, SH/4 of Sec. 2	7, _T 21-s,	R. 37-E N	. м. р. м
Paddock Field,	Lea		
The dates of this work were as follows:			
		Sentember 20.	1048
DETAILED ACCOUNT OF Total depth 5245' Lime. Ran and 54 joints of 5" OD Grade W/200 sacks cement. Cement a	obtained. (Cross out incorrect WORK DONE AND RESULTS 87 joints of 5½ 0D ca N-80 extreme line from set 72 hrs. Tested W/1	words.) OBTAINED Using from surface 1 3493! to 5200!.	to 349; Cement
Total depth 5245' Lime. Ran and 54 joints of 5" OD Grade W/200 sacks cement. Cement a Test CK. Preparing to tube w	obtained. (Cross out incorrect WORK DONE AND RESULTS 87 joints of 5½ 0D ca N-80 extreme line from set 72 hrs. Tested W/1 well.	words.) OBTAINED LSING from surface 3493! to 5200!. L500# pressure for	to 3493 Cemente 30 min.
DETAILED ACCOUNT OF Total depth 5245 Lime. Ran and 54 joints of 5" OD Grade W/200 sacks cement. Cement a Test CK. Preparing to tube w	obtained. (Cross out incorrect WORK DONE AND RESULTS 87 joints of 5½ 0D ca N-80 extreme line from set 72 hrs. Tested W/1	words.) OBTAINED Using from surface 1 3493! to 5200!. L500# pressure for	to 3493 Cemente
Total depth 5245' Line. Ran and 54 joints of 5" OD Grade W/200 sacks cement. Cement a Test CK. Preparing to tube with the subscribed and sworn before me this 21	WORK DONE AND RESULTS 87 joints of 5½ 0D ca N-80 extreme line from set 72 hrs. Tested W/1 well. The Ohio Oil Company I hereby swear or affirm is true and correct is true and correct results Position Superint Company Company Representing The Comp	words.) OBTAINED LSING from surface 1 3493' to 5200'. L500# pressure for Engine	to 349; Cements 30 min
Total depth 5245 Line. Ran and 54 joints of 5 OD Grade W/200 sacks coment. Cement a Test CK. Preparing to tube we with the same of the sacks coment of the sacks coment. Cement a test CK. Preparing to tube we with the sacks of	WORK DONE AND RESULTS 87 joints of 5½ 0D ca N-80 extreme line from set 72 hrs. Tested W/1 well. The Ohio Oil Company I hereby swear or affirm is true and correct is true and correct results Position Superint Company Company Representing The Comp	e words.) OBTAINED Lesing from surface 1 3493! to 5200!. L500# pressure for m that the information gendent Ohio Oil Company any or Operator	to 3493 Cemente 30 min.