

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER) <b>Fracture Treat</b>	<b>X</b>

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico

November 22, 1957

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Gulf Oil Corporation

J. N. Carson "A"

Well No. 1

K

(Company or Operator)

in (Unit)

NE

SW

1/4

1/4 of Sec. 28

T.

T-21-S

R.

37-E

NMPM,

Pemrose-Skally

Pool

(40-acre Subdivision)

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to fracture treat as follows:

1. Kill well with pit water; install control equipment if necessary.
2. Pull tubing, run steel line measurement to 3780', clean out with sand pump if necessary.
3. Run 2-7/8" OD tubing & Lynes formation packer; set packer at approximately 3630'.
4. Break formation w/ lease oil. Fracture treat the open hole interval from 3630-3780' with 8,000 gallons refined oil with 1# sand per gallon; inject moth balls in oil to form block and then treat with an additional 8,000 gallons refined oil with 1# sand per gallon. Flush and overflush each stage with 85 barrels oil.
5. Pull 2-7/8" OD tubing and packer; re-run 2-3/8" OD tubing same as before.
6. Sumb & test; return well to production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

Gulf Oil Corporation

Company or Operator

By.....

Position..... Area Supt. of Production

Send Communications regarding well to:

Name.....

Gulf Oil Corporation

Address.....

Box 2167 - Hobbs, New Mexico