## ENERGY AND MINERALS DEPARTMENT

	1	
MOITURIBIZED		T -
BANTA FE		i —
FILE	1	-
U.S.O.S.		
LAND OFFICE	1	-
OPERATOR		-

## P. O. BOX 2088 SANTA FE, NEW MEXICO 87501

Fo	rn)	c-	103	
Re	v 1 s	e d	10-	1 - 7

LAND OFFICE	Sa. Indicate Type of Leuse
OPERATOR	State Fon X
	5. State Oti & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS	MITTERITIES
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
	7, Unit Agreement Name
WELL SAS WELL OTHER.	
12. Name of Operator	Central Drinkard Unit
Gulf Oil Corporation	8. Farm or Lease Name
13. Address of Operator	
Poy 670 Nobb - 104 00040	9. Well No.
Box 670, Hobbs, NM 88240	102
	10, Fleid and Pool, or Wildcat
UNIT LETTER B . 554 FEET FROM THE NORTH LINE AND 2086 FEET FROM	Designation
	mmmmmmm
THE East LINE, SECTION 28 TOWNSHIP 21S RANGE 37E HMPM	
TOWNSHIP ZED RANGE J/E HMPM	
15. Elevation (Show whether DF, RT, GR, etc.)	
<b>~ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \</b>	12. County
3457' GL	Lea
Check Appropriate Box To Indicate Nature of Notice, Report or Ot	her Data
NOTICE OF INTENTION TO:	T REPORT OF:
	REPORT OF:
PERFORM REMEDIAL WORK	
	ALTERING CASING
PULL DA ALTER CASING CHANGE PLANS	PLUG AND ABANDOHMENT
CHANGE PLANS CASING TEST AND CEMENT JOB	
OTHER Repair Pressure	
	·
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.	
work) SEE RULE 1103.	estimated date of starting any proposed
POH with production equipment. Set RBP at 3000', test 500# F	lace 10' frac
POH with production equipment. Set RBP at 3000', test 500#. Feat on RBP. Circulate casing. Perf at 2850' with (4) k" TH o	Λ <sup>0</sup> -1
Establish circulation. Set cement retainer at 2700' togt tube	O phase.
Establish circulation. Set cement retainer at 2700' togt tube	O phase.
Establish circulation. Set cement retainer at 2700', test tubi  Pump 500 sacks Class "C" with 4% gel. 100 sacks Class "C" post	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer.	O phase.
Establish circulation. Set cement retainer at 2700', test tubi  Pump 500 sacks Class "C" with 4% gel. 100 sacks Class "C" post	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer. Wash sand off RBP and POH. GIH with production equipment.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer. Wash sand off RBP and POH. GIH with production equipment.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubit Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer. Wash sand off RBP and POH. GIH with production equipment.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubi Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer. Wash sand off RBP and POH. GIH with production equipment.	0° phase. ng 3000#. Squeeze.
Establish circulation. Set cement retainer at 2700', test tubit Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer. Wash sand off RBP and POH. GIH with production equipment.	0° phase. ng 3000#. Squeeze. Test casing 500#.
Establish circulation. Set cement retainer at 2700', test tubit Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer. Wash sand off RBP and POH. GIH with production equipment.  18.1 hereby certify that the information above is true and complete to the best of my knowledge and belief.  CRIGINAL SIGNED BY	0° phase. ng 3000#. Squeeze. Test casing 500#.
Establish circulation. Set cement retainer at 2700', test tubit Pump 500 sacks Class "C" with 4% gel, 100 sacks Class "C" neat. Reverse excess cement. Drill out cement and cement retainer. Wash sand off RBP and POH. GIH with production equipment.	0° phase. ng 3000#. Squeeze. Test casing 500#.

NOV 9 1982