

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
En. , Minerals and Natural Resources Department.

Form C-105
Revised 1-1-89

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-06848
5. Indicate Type of Lease	STATE ☐ FEE ☒
6. State Oil & Gas Lease No.	

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:	OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐
b. Type of Completion:	NEW WELL ☐ WORK OVER ☐ DEEPEN ☒ PLUG BACK ☐ DIFF RESVR ☐ OTHER ☐

2. Name of Operator
Chevron U.S.A Inc.

3. Address of Operator
P.O. Box 670, Hobbs, NM 88240

4. Well Location

Unit Letter A : 660 Feet From The North Line and 660 Feet From The East Line
Section 28 Township 21S Range 37E NMPM Lea County

10. Date Spudded 12-31-48	11. Date T.D. Reached 3-6-49	12. Date Compl. (Ready to Prod.) 05-16-90	13. Elevations (DF & RKB, RT, GR, etc.) 3441' GL	14. Elev. Casinghead
------------------------------	---------------------------------	--	---	----------------------

15. Total Depth 7975'	16. Plug Back T.D. 5385'	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By Rotary Tools	Cable Tools
--------------------------	-----------------------------	--	--	-------------

19. Producing Interval(s), of this completion - Top, Bottom, Name
TOP-5120 BTM-5184 Paddock

21. Type Electric and Other Logs Run

22. Was Directional Survey Made

23. Was Well Cored

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13 3/8"	48#	311'	17 1/4"	300 SX	Circ
9 5/8"	36#	2800'	12 1/4"	1300 SX (TOC @ 1275')	
7" "	26 & 23#	7747'	8 3/4"	700 SX (TOC @ 3175')	

LINER RECORD				TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET
					2 3/8"	5245'

26. Perforation record (interval, size, and number) 5120-5184' 2 JHPF 90 DEG 54 TTL HOLES				27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
				DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
				5120-5184	3000 Gal 15% NEFE

PRODUCTION

28. Date First Production 05-16-90		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping				Well Status (Prod. or Shut-in) Prod.	
Date of Test 05-21-90	Hours Tested 24	Choke Size 2" WO	Prod'n For Test Period	Oil - Bbl. 29	Gas - MCF 89	Water - Bbl. 14	Gas - Oil Ratio 3068.97
Flow Tubing Pres. 42#	Casing Pressure 30#	Calculated 24-Hour Rate	Oil - Bbl. 29	Gas - MCF 89	Water - Bbl. 14	Oil Gravity - API - (Corr.) 34.6 @ 72°	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
Sold

30. List Attachments

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature MEa 5/14/90 Printed Name C. L. Morrill Title Area Prod. Supt. Date 05-31-90

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____ 1210'
T. Salt _____
B. Salt _____ 2420'
T. Yates _____ 2580'
T. 7 Rivers _____
T. Queen _____
T. Grayburg _____
T. San Andres _____ 3870'
T. Glorieta _____ 5095'
T. Paddock _____ 5120'
T. Blinberry _____
T. Tubb _____ 6110'
T. Drinkard _____
T. Abo _____
T. Wolfcamp _____
T. Penn _____
T. Cisco (Bough C) _____

T. Canyon _____
T. Strawn _____
T. Atoka _____
T. Miss _____
T. Devonian _____
T. Silurian _____
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____
T. Delaware Sand _____
T. Bone Springs _____
T. _____
T. _____
T. _____
T. _____

Northwestern New Mexico

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn "A" _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Otzite _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____
No. 2, from _____ to _____

No. 3, from _____ to _____
No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
No. 2, from _____ to _____ feet
No. 3, from _____ to _____ feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0'	165'		surface sand	7379'	7413'		lime
	315'		red bed		7414'		sand & shale
	400'		red bed		7415'		lime
	747'		red bed, shale & shells		7444'		sand, shale & lime
	1060'		red bed		7491'		lime & sand
	1208'		red bed & shells		7492'		sand, shale, lime
	1325'		anhydrite		7497'		sand
	1520'		salt & shells		7545'		sand & lime
	2011'		salt & anhydrite		7556'		lime
	2150'		salt & shells		7578'		shale & sand
	2422'		salt & anhydrite		7595'		lime, shale, sand
	2589'		anhydrite		7659'		lime & shale
	2620'		anhydrite & shale		7677'		shale & lime
	2801'		anhydrite		7699'		shale, lime & sand
	2835'		anhydrite & lime		7716'		lime & sand
	3015'		anhydrite & shale		7723'		lime
	3075'		lime		7748'		lime & dolomite
	3276'		anhydrite, shale, & lime		7950'		dolomite
	3338'		lime		7970'		sand
	3524'		shale, anhydrite & lime		7975'		granite
	7363'		lime				

RECEIVED

JUN 04 1990

HOBBS