

AREA 640 ACRES
LOCATE WELL CORRECTLYNEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Gulf Oil Corporation Hobbs, New Mexico
Company or Operator Address
Eunice King Well No. **15** in **S2 NW** of Sec. **28**, T. **21S**
Lease
R. **37E**, N. M. P. M. **Brunson** Field, **East** **Lea** County.
Well is **2086** feet south of the North line and **2,086** feet ~~west~~ **East** of the ~~East~~ line of **Section 28**
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is **W. H. Turner** Address **Eunice, New Mexico**
If Government land the permittee is Address
The Lessee is **Gulf Oil Corporation - Gypsy Division** Address **Tulsa, Oklahoma**
Drilling commenced **March 15** 19 **49** Drilling was completed **May 12** 19 **49**
Name of drilling contractor **Two States Drilling Company** Address **Dallas, Texas**
Elevation above sea level at top of casing **3461** feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from **5100** to **5300** No. 4, from **7942** to **8135**
No. 2, from **6470** to **6600** No. 5, from to
No. 3, from **7510** to **7710** No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to **(ROTARY TOOLS)** feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	OUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
13 3/8"	48#	8 Rd	SS	275'					
9 5/8"	36#	"	"	2785'					
7"	23# & 26#	"	"	7929'					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/4"	13 3/8"	291'	300	HOMCO		
12 1/4"	9 5/8"	2800'	1300	"		
8 3/4"	7"	7942'	700	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		None				

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from **0** feet to **8146** feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing **May 12** 19 **49**
The production of the first **9 1/2** hours was **646** barrels of fluid of which **100** % was oil; %
emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas.
Rock pressure, lbs. per sq. in.

EMPLOYEES

Two States Drilling Company, Driller, Driller
Driller, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this **18th**day of **May**, 19 **49**

[Signature]
Notary Public

My Commission expires **10-24-49**Hobbs, New Mexico **May 18, 1949**Name **E. J. Gallagher**Position **District Capt**Representing **Gulf Oil Corporation**

Company or Operator

Address **Box 1667, Hobbs, New Mexico**

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	30		Caliche
	295		Redbeds and shells
	966		Redbeds
	1200		Redbeds and shells
	1280		Anhydrite
	1880		Anhydrite and salt
	2180		Anhydrite, salt and shells
	2415		Salt and shells
	2490		Anhydrite
	2544		Anhydrite and shells
	2801		Anhydrite
	3442		Anhydrite
	3528		Anhydrite and lime
	7287		Lime
	7336		Lime and shale
	7442		Lime
	7493		Lime and shale
	7670		Lime
	7695		Lime and shale
	7746		Lime
	7766		Shale
	7810		Lime
	7831		Lime and shale
	7844		Lime
	7897		Lime and shale
	7915		Lime
	7922		Lime and shale
	7943		Lime
	8146		Lime
			<u>FORMATION TOPS</u>
			Anhydrite 1200'
			Base salt 2410
			White lime 3850
			Oil pay 7942 to 8135