

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Gulf Oil Corporation	8. Farm or Lease Name Eunice King
3. Address of Operator Box 670, Hobbs, New Mexico 88240	9. Well No. 18
4. Location of Well UNIT LETTER <u>E</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>28</u> TOWNSHIP <u>21-S</u> RANGE <u>37-E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3468' CL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <u>Abandon Undesignated Montoya and complete in Paddock</u> <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7394' PB.

Pull producing equipment. Set CI BP at 7240' and cap with 35' of cement, abandoning Montoya perforations 7293' to 7338'. Set CI BP at 5350'. Squeeze old Paddock perforations 5129' to 5190' with 200 sacks of Class C cement. WOC 18 hours. Run 6-1/8" bit and clean out to CI BP at 5350'. Test casing and BP with 500#, 30 minutes. Perforate Paddock zone in 7" casing with 2, 1/2" JHPF at approximately 5292' to 5302'. Treat new perforations with 2500 gallons of 15% NE acid. Flush with brine water. Swab and clean up and place well on production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED K. J. Bruzsek TITLE Area Engineer DATE May 29, 1973

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: