

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION to (OTHER) Repair Casing Leak X		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)December 6, 1955
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Gulf Oil Corporation Eunice King Well No. 18 in E
(Company or Operator) Lease (Unit)
SW 1/4 NW 1/4 of Sec. 28, T. 21-S, R. 37-E, NMPM, Brunson Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Propose to repair leak in 7" casing as follows:

1. Pull rods, pump and tubing.
2. Set magnesium bridge plug on electric line in base of 7" casing. Dump one sack cement on plug.
3. Run tubing with HRC tool. Locate leak interval and attempt to circulate out bradenhead.
4. If leak is found above depth of 4200', perforate 2, 1/2" jet holes at 4200' and attempt to circulate out bradenhead.
5. Run cement retainer on tubing and set above perforations. Cement below retainer with sufficient volume to circulate out bradenhead and perform bradenhead squeeze. WOC.
6. Drill out retainer and cement pressure testing casing at intervals. If casing tests O.K., drill out bridge plug.
7. Rerun tubing, rods and pump. Return well to production.

Approved _____, 19____
Except as follows:Gulf Oil Corporation
Company or Operator
By _____Position _____ Area Supt. of Prod.
Send Communications regarding well to:Approved _____
OIL CONSERVATION COMMISSION
By _____

Name _____ Gulf Oil Corporation

Title _____

Address _____ Box 2167, Hobbs, N. M.