

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in **TRIPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the reason by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	X

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)April 29, 1953
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

SUNRAY OIL CORPORATION
(Company or Operator)

V. Llinam

Well No. 3 in A
(Unit)NE 1/4 NE 1/4 of Sec. 29, T. 21N, R. 37W, NMPM, Drinkard Pool
(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Llinam #3 was plugged as a dry hole, McKee Sand well, in April 1951. Subsequent information on the Continental Maryantz #1-A proves that the Abo (Chichita-Albany) production is a distinct possibility in the Llinam #3.

The following pipe was left in the well, 315', 13 3/8, R-80, 72# new casing, circulated to top with 300 sacks cement, 2850', 9 5/8, J-55, new casing, circulated to top with 1800 sacks, 60' Jol and 200 sacks straight cement.

The plan to move in rotary work-over rig to drill plug and clean out to 7500'. Run Schlumberger Micro Log from 5550' to 6400' and 6950' to 7300'. Run 5 1/2" casing and packer shoe and float collar. Cement with 125 sacks of cement. Perforate zones of probability according to micro log. At least one test in Abo and possible test in lineb. and Hobbs for production. Prepare for collection in productive zone.

Approved..... APR 30 1953....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

SUNRAY OIL CORPORATION
Company or Operator

By.....

Position.....

Send Communications regarding well to:

Name.....

Address.....