Form C-102 NEW MEXICO OIL COM Santa, Fe MISCELLANE Shmit this folice in triplicate to the Oil Conservation of to begin A copy will be returned to the sender on whi sidered advisatio, or the rejection by the Commission o be followed, and work should not begin until approval Begulations of the Commission	A, New Mexico COUS NOTICES MAR 29 1951 Commission or its proper agent before the work so ch will be given the approval, with a property r agent, of the plan ubmit of the plan ubmit of the plan ubmit of the plan ubmit of the plan as approv- 's obtained. See additional instruction file the the plan to the plan ubmit of the plan to the pl	necified hons o ved sho
negulations of the Commission,	btice by checking belows	tares
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR	
NOTICE OF INTENTION TO REPAIR WELL	OTHERWISE ALTER CASING NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		X
Hobbs New Meri	ico March 29, 1951 Place Date	
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Gentlemen:		
Following is a notice of intention to do certain work as d Sunray Oil Corporation	lescribed below at the	- 0 30
of Sec. 29 , T. 215 , R. 37E	, N. M. P. M., Drinkard	Fie
FOLLOW INSTRUCTIONS IN THE RULES The above well ran 110' low from the	OPOSED PLAN OF WORK AND REGULATIONS OF THE COMMISSION south off-set and 200' low from the	
FOLLOW INSTRUCTIONS IN THE RULES	S AND REGULATIONS OF THE COMMISSION south off-set and 200' low from the '. A Drill Stem Test was taken with to stands of oil and gas cut mud, and tion to plug the well as follows. a cement plug will be placed over capped with a 50' cement plug from culated with 300 sacks.	
FOLLOW INSTRUCTIONS IN THE RULES The above well ran 110' low from the east off-set at a total depth of 7941 the packer set at 7929', recovered tw 1080' of salt water. It is our inten The well will be filled with 9# mud, the Drinkard Fay and the well will be which will protrude 4' of 4" pipe. 13 3/8 N/80, 72 pd. set at 315', Circ 9 5/8, J-55, 32.3 pd. set at 2850', C No pipe will be pulled. 50 Saks of cement will be placed in	SAND REGULATIONS OF THE COMMISSION south off-set and 200' low from the .'. A Drill Stem Test was taken with to stands of oil and gas cut mud, and tion to plug the well as follows. a cement plug will be placed over capped with a 50' cement plug from culated with 300 sacks. Dirculated with 1800 sacks. the bottom of the hole to protect SUNRAY OIL CORPORATION By	
FOLLOW INSTRUCTIONS IN THE RULES The above well ran 110' low from the east off-set at a total depth of 7941 the packer set at 7929', recovered tw 1080' of salt water. It is our inten The well will be filled with 9# mud, the Drinkard Fay and the well will be which will protrude 4' of 4" pipe. 13 3/8 N/80, 72 pd. set at 315', Circo 9 5/8, J-55, 32.3 pd. set at 2850', O No pipe will be pulled. 50 Sacks of cement will be placed in the McKee Sand. MAX 29 1951 19 except as follows:	SAND REGULATIONS OF THE COMMISSION south off-set and 200' low from the '. A Drill Stem Test was taken with to stands of oil and gas cut mud, and tion to plug the well as follows. a cement plug will be placed over capped with a 50' cement plug from culated with 300 sacks. Dirculated with 1800 sacks. the bottom of the hole to protect SUNRAY OIL CORPORATION By Company or Operator By District Superintendent Send communications regarding well to	
FOLLOW INSTRUCTIONS IN THE RULES The above well ran 110' low from the east off-set at a total depth of 7941 the packer set at 7929', recovered tw 1080' of salt water. It is our inten The well will be filled with 9# mud, the Drinkard Fay and the well will be which will protrude 4' of 4" pipe. 13 3/8 N/80, 72 pd. set at 315', Circo 9 5/8, J-55, 32.3 pd. set at 2850', C No pipe will be pulled. 50 Sakes of cement will be placed in the McKee Sand. MAX 29 1951 19	SAND REGULATIONS OF THE COMMISSION south off-set and 200' low from the .'. A Drill Stem Test was taken with to stands of oil and gas cut mud, and tion to plug the well as follows. a cement plug will be placed over capped with a 50' cement plug from culated with 300 sacks. Dirculated with 1800 sacks. the bottom of the hole to protect SUNRAY OIL CORPORATION By Company or Operator By District Superintendent	-

. ^د ,



and the second second

a franciska Alexandro fran

à

Provide the day

