.....

Address Box 2167, Hobbs, N. M.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See addi-

Indicate Nature of Notice by Checking Belo

NOTICE OF INTENTION TO CHANGE PLANS		1			
		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		Notice of Intention to Drill Deeper	
Notice of Intention to Plug Well		Notice of Intention to Plug Back		NOTICE OF INTENTION	
Notice of Intention to Squeeze		Notice of Intention to Acidize		TO SET LINER NOTICE OF INTENTION	X
NOTICE OF INTENTION TO GUN PERFORATE	X	Notice of Intention (Other)		TO SHOOT (Nitro)	
OIL CONSERVATION CO				(OTHER)	
SANTA FE, NEW MEXICO	D D D D D D D D D D D D D D D D D D D	Kahla H	. 34 .		
		Hobbs, New (Place)	Mexico	October 12,	1954
Gentlemen:				(Date)	
Following is a New	- .				
- ononing is a Notice of	Intention to do	certain work as described below at	the	Bunice King	
(Con	DBBBY OF OBSER			A 1	
SW 1/4 NW 1/4 (of Sec 28	, T. 21– S , R. 37– E	······································	Vell No	E
(40-acre Subdivision)		, 1, R	, ,NMPM.,	Hare	(Unit)
Lea	Cour	ity.			
1. Pull tubing 2. Drill from	g and rods.	include Connell Sand as	follows:	WORK GULATIONS)	
 Drill from Run Schlumb Underream of Run approxi Cement casi Clean out t Perforate 1 Run hookwall with 3000 c 	plugged ba perger ES a ppen hole t inately 190 ng with 4 o fleat sh intr oppos 1 packer a allons from	ick total depth 7875' to and Microlog Surveys. 0 8-1/4". ' 5-1/2" 17# J-55 SS ca Gel cement. os. ite Connell Sand from in nd hydraulic holddown.	follows: 8030'. sing to s nterpreta Test Cor	set from 7870-8()60 [*] . ation of legs. anell Sand and treat	
 Drill from Run Schlumb Underream of Run approxi Cement casi Clean out t Perforate 1 Run hookwall with 3000 c 	plugged ba perger ES a ppen hole t inately 190 ng with 4 o fleat sh intr oppos 1 packer a allons from	ick total depth 7875' to and Microlog Surveys. 0 8-1/4". ' 5-1/2" 17# J-55 SS ca Gel cement. os. ite Connell Sand from in nd hydraulic holddown.	follows: 8030'. sing to s nterpreta Test Cor	set from 7870-8()60 [*] . ation of legs. anell Sand and treat	
 Drill from Run Schlumb Underream of Run approxi Cement casi Clean out t Perforate 1 Run hookwall with 3000 c 	plugged ba perger ES a ppen hole t inately 190 ng with 4 o fleat sh intr oppos 1 packer a allons from	ick total depth 7875' to and Microlog Surveys. © 8-1/4". " 5-1/2" 17# J-55 SS ca Gel cement. os. ite Connell Sand from in the budges lie budget	follows: 8030'. sing to s nterpreta Test Cor	set from 7870-8()60 [*] . ation of legs. anell Sand and treat	
 Drill from Run Schlumb Underream of Run approxi Cement casi Clean out t Perforate 1 Run hookwall with 3000 c 	plugged ba perger ES a ppen hole t inately 190 ng with 4 o fleat sh intr oppos 1 packer a allons from	ick total depth 7875' to and Microlog Surveys. 0 8-1/4". ' 5-1/2" 17# J-55 SS ca Gel cement. os. ite Connell Sand from in nd hydraulic holddown.	follows: 8030'. sing to s nterpreta Test Cor	set from 7870-8()60 [*] . ation of legs. anell Sand and treat	
 Drill from Run Schlunk Underream of Run approxi Cement casi Clean out t Perforate 1 Run hookwall with 3000 gi Pull packer 	plugged ba perger ES a ppen hole t inately 190 ing with 420 o fleat sh intr oppos l packer a allons fra and produc	ack total depth 7875' to and Microlog Surveys. >>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	follows: 8030'. sing to s nterpreta Test Cor	set from 7870-8()60 [*] . ation of legs. anell Sand and treat	
 Drill from Run Schlunk Underream of Run approxi Cement casi Clean out t Perforate 1 Run hookwall with 3000 c 	plugged ba perger ES a ppen hole t inately 190 ing with 420 o fleat sh intr oppos l packer a allons fra and produc	ack total depth 7875' to and Microlog Surveys. >>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	follows: 8030'. sing to s nterpret: Test Cor nes toget	s et from 7870-8060'. ation of legs. nuell Sand and treat ther.	
 Drill from Run Schlunk Underream of Run approxi Cement casi Clean out t Perforate 1 Run hookwall with 3000 gi Pull packer 	plugged ba perger ES a ppen hole t inately 190 ing with 420 o fleat sh intr oppos l packer a allons fra and produc	ack total depth 7875' to and Microlog Surveys. o 8-1/4". ' 5-1/2" 17# J-55 SS ca Gel cement. oe. ite Connell Sand from i nd hydraulic holddown. c if warranted. ce McKee and Connell Zon	follows: 8030'. sing to s nterpret: Test Cor nes toget	s et f.rom 7870-8060'. ation of legs. nnell Sand and treat ther.	
 Drill from Run Schlunk Underream of Run approxi Cement casi Clean out t Perforate 1 Run hookwall with 3000 g Pull packer 	plugged ba perger ES a ppen hole t inately 190 ing with 420 o fleat sh intr oppos l packer a allons fra and produc	ack total depth 7875' to and Microlog Surveys. >>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	follows: 8030'. sing to s nterpret: Test Cor nes toget	s et from 7870-8060'. ation of legs. nuell Sand and treat ther.	
 Drill from Run Schlunk Underream of Run approxi Cement casi Clean out t Perforate 1 Run hookwal: with 3000 gi Pull packer 	plugged ba perger ES a ppen hole t inately 190 ing with 420 o fleat sh intr oppos l packer a allons fra and produc	ack total depth 7875' to and Microlog Surveys. o 8-1/4". ' 5-1/2" 17# J-55 SS ca Gel cement. oe. ite Connell S _a nd from i nd hydraulic holddown. c if warranted. ce McKee and Connell Zon By	follows: 8030'. sing to s nterpreta Test Cor nes toget Gulf O	s et from 7870-8060 ¹ . ation of legs. numell Sand and treat ther. <u>Company or Operator</u>	
 Drill from Run Schlunk Underream of Run approxi Cement casi Clean out t Perforate 1 Run hookwall with 3000 gi Pull packer 	plugged ba perger ES a ppen hole t inately 190 ing with 420 o fleat sh intr oppos l packer a allons fra and produc	ack total depth 7875' to and Microlog Surveys. o 8-1/4". ' 5-1/2" 17# J-55 SS ca Gel cement. oe. ite Connell S _a nd from i nd hydraulic holddown. c if warranted. ce McKee and Connell Zon By	follows: 8030'. sing to s nterpreta Test Cor nes toget Gulf O	s et f.rom 7870-8060'. ation of legs. nnell Sand and treat ther.	
 Drill from Run Schlunk Underream of Run approxi Cement casi Clean out t Perforate 1 Run hookwal: with 3000 gi Pull packer 	plugged ba perger ES a ppen hole t inately 190 ing with 420 o fleat sh intr oppos l packer a allons fra and produc	ack total depth 7875' to and Microlog Surveys. o 8-1/4". ' 5-1/2" 17# J-55 SS ca Gel cement. oe. ite Connell S _a nd from i nd hydraulic holddown. c if warranted. ce McKee and Connell Zon By	follows: 8030'. sing to s nterpreta Test Con nes toget Gulf O Area St Send Comm	s et from 7870-8060 ¹ . ation of legs. numell Sand and treat ther. <u>Company or Operator</u>	

Title.....