State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

2040 Pacheco St. Santa Fe, NM 87505					30-025-06872				
P.O. Drawer DD, Artesia, NM 88210					sIndicate Type of Lease				
					21	STATE	FEE		
<u>DISTRICT III</u> 1000 Rio Brazos Rd., Aztec, NM 87410						sState Oil & Gas Lease No.			
01.11	IDDV NOTIO		0070 01111						
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A									
l ·	RENT RESERVO	IR. USE "APPL	ICATION FOR PE		,	TLease Name or Unit	t Agreement Name		
	(FORM C-10	1) FOR SUCH P	PROPOSALS.)			2. 0. 0. 110011			
Type of Well:	GAS 🔽								
WELL	WELL X		OTHER			NA 1 - 1/2 A 1 -			
₂Name of Operator TITAN RESOURCES	I, INC.					₃Welf No. 18			
sAddress of Operator 500 WEST TEXAS, SUITE 500, MIDLAND, TEXAS 79701						Pool name or Wildcat			
4Well Location	DITE 500, MIDE	AND, TEXAS	79701			BLINEBRY?	<u> raddo</u>	-15	
Unit Letter M	. 760 _{Fe}	et From The	WEST	Line and	660	E	SOUTH		
Offit Letter	re	etrion the		Line and		Feet From The		Line	
Section	28	Township	218	Range	37E	NM PM	LEA (County	
		₁₀Elevatio 3476 G	n (Show whether DF R	, RKB, RT, GR, et	C.)				
11	Check Appr	opriate Box	to Indicate N	ature of Not	ice. Rep	ort. or Other [Data		
Check Appropriate Box to Indicate Nature of Notice, Rep NOTICE OF INTENTION TO: SUBS						SEQUENT REPORT OF:			
PERFORM REMEDIAL WORK		PLUG AND A		REMEDIAL WO			ALTERING CASING	, –	
TEMPORARILY ABANDON		CHANGE PLA		COMMENCE		NS	PLUG AND ANBANI		
PULL OR ALTER CASING				CASING TEST			LOG AND ANDANI	JOHNERT	
	i					[]		_	
OTHER:				OTUED:				1	
OTHER:				1					
12Describe Proposed or Comp	leted Operations (C	learly state all pert	linent details, and giv	1					
Describe Proposed or Comp work) SEE RULE 1103. TD: 8175' PBTD: 497	75' Elevation:			1					
12Describe Proposed or Comp work) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @	75' Elevation:			1					
Describe Proposed or Comp work) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J- 5-1/2" 17# J-	75' Elevation:	3462' GL, 347		1					
12Describe Proposed or Comp work) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J-	75' Elevation: 320' circ 55 @2853'	3462' GL, 347		1					
Describe Proposed or Comp work) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J- 5-1/2" 17# J- Perfs: 3838'-3903' Recommended procedu	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/	3462' GL, 347		1					
raDescribe Proposed or Comp work) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J- 5-1/2" 17# J- Perfs: 3838'-3903' Recommended procedi 1) MIRU. Install BOP.	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg.	3462' GL, 347		1					
Describe Proposed or Comp work) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J- 5-1/2" 17# J- Perfs: 3838'-3903' Recommended procedi 1) MIRU. Install BOP. 2) Set CIBP @ 3800', 6 3) RIH w/ tbg & spot 15	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg. cap w/ 35' cmt.	3462' GL, 347 cmt 1830'	'6' KB	e pertinent dates,	including esti	mated date of starting	any proposed		
Describe Proposed or Comp work) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J- 5-1/2" 17# J- Perfs: 3838'-3903' Recommended procedi 1) MIRU. Install BOP. 2) Set CIBP @ 3800', 6 3) RIH w/ tbg & spot 15 4) Perf 5-1/2" csg @ 35	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg. cap w/ 35' cmt. 5 sx cmt plug 29	3462' GL, 347 cmt 1830'	'6' KB	e pertinent dates,	including esti	mated date of starting	any proposed		
Describe Proposed or Comp work) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J- 5-1/2" 17# J- Perfs: 3838'-3903' Recommended procedi 1) MIRU. Install BOP. 2) Set CIBP @ 3800', 6 3) RIH w/ tbg & spot 15	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg. cap w/ 35' cmt. 5 sx cmt plug 29 50'. RIH w/ pkr	3462' GL, 347 cmt 1830' 100-2800'. & tbg. Set pkr	6' KB @ 200'. Pump	Te pertinent dates,	including esti . Displace	mated date of starting	any proposed e 5-1/2" csg.		
Describe Proposed or Comp work) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J- 5-1/2" 17# J- Perfs: 3838'-3903' Recommended procedd 1) MIRU. Install BOP. 2) Set CIBP @ 3800', 6 3) RIH w/ tbg & spot 18 4) Perf 5-1/2" csg @ 36 5) Spot 10 sx plug @ s	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg. cap w/ 35' cmt. 5 sx cmt plug 29 50'. RIH w/ pkr	3462' GL, 347 cmt 1830' 100-2800'. & tbg. Set pkr	6' KB @ 200'. Pump	se pertinent dates,	including esti . Displace	cmt to 270' inside	e 5-1/2" csg.		
Recommended proceds 1) MIRU. Install BOP. 2) Set CIBP @ 3800; 63) RIH w/ tbg & spot 16 4) Perf 5-1/2" csg @ 35 5) Cut off csg head and	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg. cap w/ 35' cmt. 5 sx cmt plug 29 50'. RIH w/ pkr urface. d weld on plates	3462' GL, 347 cmt 1830' 900-2800'. & tbg. Set pkr	6' KB @ 200'. Pump	50 sx cmt plug	including esti Displace	cmt to 270' inside	any proposed 5-1/2" csg. AF NOTHER A	Ą	
Describe Proposed or Comp work) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J- 5-1/2" 17# J- Perfs: 3838'-3903' Recommended procedd 1) MIRU. Install BOP. 2) Set CIBP @ 3800', 6 3) RIH w/ tbg & spot 18 4) Perf 5-1/2" csg @ 36 5) Spot 10 sx plug @ s	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg. cap w/ 35' cmt. 5 sx cmt plug 29 50'. RIH w/ pkr urface. d weld on plates	3462' GL, 347 cmt 1830' 900-2800'. & tbg. Set pkr	6' KB @ 200'. Pump	For each of the pertinent dates, so that the pertinent dates, so the pertinent dates dates and so the pertinent dates.	Displace	cmt to 270' inside	e 5-1/2" csg.	Ą	
Recommended procedured in Spet 119 and	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg. cap w/ 35' cmt. 5 sx cmt plug 29 50'. RIH w/ pkr urface. d weld on plates	3462' GL, 347 cmt 1830' 000-2800'. & tbg. Set pkr s. Install dry ho	6' KB @ 200'. Pump ole marker.	50 sx cmt plug	including esti Displace	cmt to 270' inside	any proposed 5-1/2" csg. AF NOTHER A	Ą	
Describe Proposed or Compwork) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J-5-1/2" 17# J-Perfs: 3838'-3903' Recommended proceded in MIRU. Install BOP. 2) Set CIBP @ 3800', 6 3) RIH w/ tbg & spot 15 4) Perf 5-1/2" csg @ 35 5) Spot 10 sx plug @ s 6) Cut off csg head and NOTE: Mud laden fluid	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg. sap w/ 35' cmt. 5 sx cmt plug 29 50'. RIH w/ pkr urface. d weld on plates between all plu	3462' GL, 347 cmt 1830' 100-2800'. & tbg. Set pkr s. Install dry ho	6' KB @ 200'. Pump ole marker.	50 sx cmt plug	including esti Displace PECO (*** PECO (***) PECO (***) PECO (***)	cmt to 270' inside	any proposed 2 5-1/2" csg. 85 NO 3800 2 1 00 3800 5600 2	Ą	
Describe Proposed or Compwork) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J-5-1/2" 17# J-Perfs: 3838'-3903' Recommended proceded in MIRU. Install BOP. 2) Set CIBP @ 3800', 6 3) RIH w/ tbg & spot 15 4) Perf 5-1/2" csg @ 35 5) Spot 10 sx plug @ s 6) Cut off csg head and NOTE: Mud laden fluid	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg. cap w/ 35' cmt. 5 sx cmt plug 29 50'. RIH w/ pkr urface. d weld on plates	3462' GL, 347 cmt 1830' 100-2800'. & tbg. Set pkr s. Install dry ho	6' KB @ 200'. Pump ole marker.	50 sx cmt plug	including esti Displace PECO (*** PECO (***) PECO (***) PECO (***)	cmt to 270' inside	any proposed 2 5-1/2" csg. 85 NO 3800 2 1 00 3800 5600 2		
Describe Proposed or Compwork) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J-5-1/2" 17# J-Perfs: 3838'-3903' Recommended proceded in MIRU. Install BOP. 2) Set CIBP @ 3800', 6 3) RIH w/ tbg & spot 15 4) Perf 5-1/2" csg @ 35 5) Spot 10 sx plug @ s 6) Cut off csg head and NOTE: Mud laden fluid	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg. cap w/ 35' cmt. 5 sx cmt plug 29 50'. RIH w/ pkr urface. d weld on plates between all plu	3462' GL, 347 cmt 1830' 100-2800'. & tbg. Set pkr s. Install dry ho	6' KB @ 200'. Pump ole marker.	50 sx cmt plug	including esti Displace PECO (*** PECO (***) PECO (***) PECO (***)	cmt to 270' inside	any proposed 2 5-1/2" csg. 85 NO 3800 2 1 00 3800 5600 2	B	
Describe Proposed or Compwork) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J-5-1/2" 17# J-Perfs: 3838'-3903' Recommended proceded 1) MIRU. Install BOP. 2) Set CIBP @ 3800', 6 3) RIH w/ tbg & spot 15 4) Perf 5-1/2" csg @ 36 5) Spot 10 sx plug @ s 6) Cut off csg head and NOTE: Mud laden fluid	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg. cap w/ 35' cmt. 5 sx cmt plug 29 50'. RIH w/ pkr urface. d weld on plates between all plu	3462' GL, 347 cmt 1830' 100-2800'. & tbg. Set pkr s. Install dry ho	6' KB @ 200'. Pump ole marker.	50 sx cmt plug	including esti Displace PECO (*** PECO (***) PECO (***) PECO (***)	cmt to 270' inside	any proposed 85-1/2" csg. 85-1000-1000-2000-2000-2000-2000-2000-200	B	
Describe Proposed or Compwork) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J-5-1/2" 17# J-Perfs: 3838'-3903' Recommended procedi 1) MIRU. Install BOP. 2) Set CIBP @ 3800', 63 RIH w/ tbg & spot 154 Perf 5-1/2" csg @ 355 Spot 10 sx plug @ s6) Cut off csg head and NOTE: Mud laden fluid I hereby certify that the information of the signature Type or print name Laura	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg. cap w/ 35' cmt. 5 sx cmt plug 29 50'. RIH w/ pkr urface. d weld on plates between all plu nation above is true	3462' GL, 347 cmt 1830' 100-2800'. & tbg. Set pkr s. Install dry ho	6' KB @ 200'. Pump ole marker.	50 sx cmt plug	including esti Displace PECO (*** PECO (***) PECO (***) PECO (***)	cmt to 270' inside	any proposed 85-1/2" csg. 85-1000-1000-2000-2000-2000-2000-2000-200	B	
Describe Proposed or Compwork) SEE RULE 1103. TD: 8175' PBTD: 497 Casing: 13-3/8" 48# @ 8-5/8" 32# J-5-1/2" 17# J-Perfs: 3838'-3903' Recommended procedi 1) MIRU. Install BOP. 2) Set CIBP @ 3800', 63 RIH w/ tbg & spot 154 Perf 5-1/2" csg @ 355 Spot 10 sx plug @ s6) Cut off csg head and NOTE: Mud laden fluid I hereby certify that the information of the signature Type or print name Laura	75' Elevation: 320' circ 55 @2853' 55 @ 8175' T/ ure: POH w/ tbg. cap w/ 35' cmt. 5 sx cmt plug 29 50'. RIH w/ pkr urface. d weld on plates between all plu nation above is true	3462' GL, 347 cmt 1830' 100-2800'. & tbg. Set pkr i. Install dry ho	@ 200'. Pumpole marker.	50 sx cmt plug dge and belief.	Displace	cmt to 270' inside	any proposed 85-1/2" csg. 85-1000-1000-2000-2000-2000-2000-2000-200	3 498-8662	

