

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

The Ohio Oil Company Hobbs, New Mexico
Company or Operator Address
Wm. Turner Well No. 2 in NW 1 SE 1 of Sec. 29 T. 21 S
Lease
R. 37E, N. M. P. M., East Eunice Lea County.
Well is 1650 feet North of the North line and 2310 feet west of the East line of Sec. 29
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Wm. Turner Address Eunice, New Mexico
If Government land the permittee is Address
The Lessee is Address
Drilling commenced June 4, 1937 19 Drilling was completed Sept. 9, 1937 19
Name of drilling contractor National Prod & Drilg Co Address Midland, Texas
Elevation above sea level at top of casing 3475 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3700 to 3800 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13"	50			325	Reg			
8 5/8				1292	"			
7	24			2713	"			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15	13	325	150	Halliburton	10	40
10	8 5/8	1292	150	"	10	40
8 3/4	7	2713	300	"	10	40

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		3,000 gals acid		8/19		
		5,000 gals acid		8/22		

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from 0 feet to 3800 feet, and from feet to feet

PRODUCTION

Put to producing Sept 16, 1937 19
The production of the first 24 hours was 20 barrels of fluid of which 100 % was oil; %
emulsion; % water; and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

H. L. Walters, Driller L. B. Henderson, Driller
N. Scaramella, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 14th day of September, 1937
Notary Public.
My Commission expires March 2, 1941
Hobbs, New Mexico Sept. 14, 1937
Name
Position Supt
Representing The Ohio Oil Company
Address Hobbs, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	20	20	Caliche
20	35	15	Grey sand
35	80	45	Red sand
80	120	40	Quick sand
120	145	25	Yellow sand
145	175	30	Red rock
175	195	20	Green shale
195	270	75	Red rock
270	280	10	Water sand
280	285	5	Grey shale
285	305	20	Blue lime
305	325	20	Blue shale
325	330	5	Red rock
330	345	15	Hard Hyd
345	390	45	Red shale
390	420	30	Brown shale
420	430	10	Red mud
430	450	20	Lime shells
450	460	10	Red sand
460	550	90	Red shale
550	600	50	Red bed
600	625	25	Blue
625	650	25	Red rock
650	735	85	Red shale
735	745	10	Hyd hard
745	780	35	Red rock
780	860	80	Hard red sand
860	875	15	Water sand
875	895	20	Hard grey sand
895	935	40	Hard sand
935	965	30	Red sand
965	970	5	Hard sand
970	1030	60	Red sand
1030	1070	40	Red mud
1070	1095	25	Red sand
1095	1115	20	Red rock
1115	1145	30	Red rock-gyp
1145	1150	5	Red rock
1150	1175	25	Anhydrite
1175	1190	15	Red mud
1190	1250	60	Anhydrite
1250	1275	25	Hard Anhydrite
1275	1320	45	Anhydrite
1320	1405	85	Salt-Potash
1405	1495	90	Anhy-salt
1495	1580	85	Anhydrite
1580	1630	50	Anhy-salt-potash
1630	1650	20	Anhydrite
1650	1680	30	Anhy-salt-potash
1680	2045	365	Salt-anhy
2045	2070	25	Salt-potash
2070	2410	340	Anhydrite-salt
2410	2425	15	Anhydrite
2425	2465	40	Grey lime
2465	2565	100	Lime
2565	2590	25	Grey lime
2590	2650	60	Broken Lime
2650	2720	70	Lime
2720	2845	125	Broken lime
2845	3280	435	Lime
3280	3500	220	Gray lime
3500	3505	5	Blue shale
3505	3565	60	Grey lime
3565	3692	127	Lime
3692	3716	24	Hard lime
3716	3800	84	Lime