DISTRIBUTION: NFW MEXICO OCC Mr. J. A. Grimes Mr. L. H. Shearer Mr. H. J. Brunt Mr. T. A. Steele

Mr. T. O. Webb

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

Notice of Intention to Change Plans		Notice of Intention to Temporaeily Abandon Well		Notice of Intention to Drill Deeper	
Notice of Intention to Plug Well		Notice of Intention to Plug Back		Notice of Intention to Set Liner	·
Notice of Intention to Squeeze	x	Notice of Intention to Acidize	x	Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate	x	Notice of Intention (Other) Sandfrac	x	NOTICE OF INTENTION (OTHER) Dual complete	x

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

1

Hobbs, New Mexico

8-57

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the. Wm. H. Turner

THE OHIO OIL COMPANY	
(Company or Operator)	(Unit)
NE 1/4 SE 1/4 of Sec. 29 , T 2LS , R 37E	NMPM Blinebry gas
(40-acre Subdivision)	······································
Lea County.	

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

7912' TD; 5687 P.B. $5\frac{1}{2}$ " @ 7911' with 950 sx 5% (top cement by temp. survey - 5175). Plan to shut off water prod. in Blinebry gas zone & dual with Tubb gas as follows: Set bridge plug @ approx. 5500' temporarily plugging off Blinebry perfs 5570'-5620', perf $5\frac{1}{2}$ " csg @ approx. 5375' & block squeeze (probable source water prod. from overlying Penrose section entering thru cement channel or fracture behind $5\frac{1}{2}$ " csg). Drill out cement & bridge plug & test for water shut off.

Drill out cement & bridge plug @ 5687', set bridge plug approx. 6300' & perf 5½" csg opposite Tubb gas section approx. 6100'-6230' & treat with 500 gals mud acid & 10,000 gals sand/oil. Set Baker Model "D" prod. pkr @ approx. 6050', rerun 2" tbg with Garrett circ. valves above & below pkr. Swab in gas zone & complete as Blinebry (gas)/Tubb (gas) Dual.

DC Order #478 approved July 15, 1957

Approved, 19, 19	THE OLIO OIL COMPANY Company or Operator
	By SIGNED BY B. G. HOWARD
Approved OIL CONSERVATION COMMISSION	Position
By	Nanc. The Ohio Oil Company
Title	Address