

**NEW MEXICO OIL CONSERVATION COMMISSION**  
**Santa Fe, New Mexico**

**MISCELLANEOUS NOTICES**

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<b>X</b>	NOTICE OF INTENTION (OTHER) Water Frac	<b>X</b>	NOTICE OF INTENTION (OTHER) Dual Complete	<b>X</b>

OIL CONSERVATION COMMISSION  
 SANTA FE, NEW MEXICO

Hobbs, New Mexico  
 (Place)

May 12, 1958  
 (Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Pan American Petroleum Corporation

W. H. Turner Well No. 1 in P  
 (Company or Operator) Lease (Unit)  
SE 1/4 SE 1/4 of Sec. 29, T.21-S, R.37-E, NMPM, Drinkard Eumont Pool  
 (40-acre Subdivision)  
Lea County.

**FULL DETAILS OF PROPOSED PLAN OF WORK**  
 (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

In order to dual complete the above well in the Eumont Gas Pool we propose the following:

Set drillable bridge plug at 3710, perforate 3700-3702 with 4 shots per foot. Set retainer at approximately 3680 and circulate cement behind 5" casing to surface through above perforation and squeeze with 200 sacks slo-set + 4% Gel. Drill out cement and plug and set retrievable bridge plug at 3690; perforate 3520 to 3645 with 2 shots per foot, sand water frack with 40,000 gallons of water containing one pound of sand per gallon and test and return well to production. Authority to dual complete per N.M.O.C.C. Order No. DC 593.

Approved \_\_\_\_\_, 19\_\_\_\_  
 Except as follows:

Approved \_\_\_\_\_  
 OIL CONSERVATION COMMISSION

By \_\_\_\_\_  
 Title \_\_\_\_\_

Pan American Petroleum Corporation  
 Company or Operator

By R. L. Hendrickson

Position Field Superintendent  
 Send Communications regarding well to:

Name R. L. Hendrickson

Address Box 68 - Hobbs, New Mexico