This form is <u>not</u> to be used for reporting packer leakage tests in Northwest New Mexico NEW EXICO OIL CONSERVATION COMMISSI

SOUTHEAST NEW MEXICO PACKER LEAKAGE TEST

Operator			•	Leas			Well 3
	Sinclair Oil	L & Gas Sec	Company	Twp	H. S. Turner Rge	County	NO.
Location of Well			29	215	37E Method of Prod	Prod. Medium	Lea Choke Size
	Name of Rese	rvoir	or Pool	Type of Prod (Oil or Gas)	Flow, Art Lift	(Tbg or Csg)	
Upper Compl	Blinebry (Ga	_		Gas	Flow	Csg	2#
Low er Compl	Drinkard			011	Flow	Tbg	32/64"
·	<u></u>			FLOW TEST	NO. 1		
Both zon	es shut-in at	t (hour	, date):	8:00 AM 5-	-20-65		т
	ned at (hour,					Uppe r Completio	Lower on Completion
					« • • • • • • • • • • • • • • • • • •	• • • • • • •	X
							60
							Yes
							40
Minimum pressure during test							50
) • • • • • • • • • • • • • • • • • •		20
Was pres	ssure change a	an in cr	ease or a	decrease?		No chang	e Decrease
Well clo	osed at (hour			00 A M 5-22-	5 Producti		
					duction Test5		
Remarks	Results of	Tests :	Indicate th	nat packer is	seperating the two	o zones properl	y
	ened at (hour		•	FLOW TEST 8:00 A M 5-23	-65	Upper Completi X	Lowe r on Completion
							40
							Yes
					• • • • • • • • • • • • • • • • • • • •		40
							40
					· · · · · · · · · · · · · · · · · · ·		40
)		0
							se No change
				8:00 A M 5-24	-65 Productio	ne on	
	dijer i on			Gas Pro 9;During		MCF; GOR 4	545
Remarks						172	
Thereh	v certify the	t. t.he	informatio	n herein conta	ined is true and	complete to the	e best of my
knowled		-0 0116			Operator SINC		
Approve New Me	d xico Oil Con	ervati	on Commiss	19	By	ng let-	
By	-(20)	tâm	C.4		Title Senior B	ngineer	
Title			//		Date 5-26-65		
1							

INSTRUCTIONS	5 sector in the sector should be seen should approximate the should be set as the should be should be should be
A packet these test shall be commenced on each multiply completed	The second s
	θ. Στην από το το το του του το το προσφάρια. Anno 1998 was to the stated
	1997 1977 The second se
	er u d'i the treviously produced some that I real
	merte stol un some is produced.
	Y style that chall be worth could
aunication of congreter of when requested by the Commission	A design of the shall be contributed a shall be contributed as a second state of the shall be contributed as a shall be contributed as a second state of the sha
In At increasing the sould to the commencement of any packer leakage test,	Which is the standard part tester at least twice. I have the flow test the state the state of the
	hexing is the set of sach flow test.
test is to be comparated. Offset operators shall also be so notified.	8. ⊕ ≈
3. The packer leakage test shall commence when both zones of the dual	
The of the sould like the second of the the second and the second of the	The second with the state of the second
sbut in m b b. rs	
	stas The construct a pressure versus
For First set S. L. Ser come of the dual completion shall be produced	time division of the source share all prossure
	change is to be bound ing there or all prossure change is how auge charts as well as an dead- weight is an end bound taken. If the pressure chart is sub-
	whitee is a second of the decaded. It the pressure there is sub-
	office and a second the Packer Leakage Text Form
that the flow of the sof continue for more than 24 hours.	the state of the s
a section was more chain by hours.	when the
in the source of the states in the source of	when to find the set of a gasacal ratio test period.
	when the second se
	when the second
	when the second ratio test period.
	when the second
,	when the second ratio test period.
	when the test period.
	when the second state of t

1. Hereiter 3 414 : - 4 H:::: ШĦ · · · an e de de la promoce e construir e constr _____