

DIAGRAMMATIC SKETCH SHOWING
DUAL COMPLETION INSTALLATION

DRINKARD PLUGGER

Blinebry

12 3/4" Surface @ 532 w/ 300 SK.

3 1/4" Intermediate @ 2786' w/ 1000 SK.
Top Cement @ 2989' behind 5 1/2" Csg.

TOP AT 5567 FEET
NAME: BLINEBRY

COMPLETION THIS ZONE:
BOTTOM AT 5577 FEET

PERFORATED 5567-91, 5598-5626 FEET
5685-98, 5634-45

THIS ZONE PRODUCED THRU 2 1/6" OD TBG
AND SLEEVE @ 6476

SLIDING SLEEVE @ 6476 FT

Model: 10
PACKER SET AT 6500 FEET

FWP BLANKING PLUG @ 6546
(Packer Tested @ 1000 Psi for 30 min Held OK)

Bottom of TBG @ 6575.

TOP AT 6584 FEET
NAME: DRINKARD

COMPLETION THIS ZONE:
BOTTOM AT 6604 FEET

PERFORATED: 6584 - 6604 FEET

THIS ZONE TEMPORARILY ABANDONED

(To be used in a Flood Project at later date.)

5 1/2" CASING SET AT 6618 FEET
CEMENTED w/ 500 SK.
TOTAL WELL DEPTH 6618 FEET

COMPANY SINCLAIR OIL & GAS CO
LEASE H.S. TURNER WELL No. 3
FIELD DRINKARD & BLINEBRY
DATE MAY 28 1965