

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) Frac	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)March 2, 1962
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Sunray Mid-Continent Oil Company **D. Hardy** Well No. **1** in **H**
(Company or Operator) (Unit)
Lease
SE $\frac{1}{4}$ **No** $\frac{1}{4}$ of Sec. **29**, T. **21S**, R. **37E**, NMPM, **Drinkard** Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Move in pulling unit. Kill Drinkard with oil.
2. Remove tbghd and install bop. Lower tbg to bottom to check for sand fill-up. If necessary run bit and clean out.
3. Run and set Baker FB pkr @ approximately 6450' on 2 7/8" tubing.
4. Frac Drinkard with total of 2000 gal LTNE acid for spearheads and 20,000 gals refined oil w/J105 and 1200# rock salt if pressures permit.
5. Flush tubing and overflush formation with 50 BO.
6. Leave well shut-in 24 hours or until pressure bleeds off ~~with~~ whichever is the shorter time. Pull 2 3/8" tubing and packer when pressure permits. Check sand fill and reverse circ if necessary.
7. Run 2 3/8" tubing with seating nipple, mud anchor, and scalloped collar.
8. Swab well until flowing and test.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy.....
Title.....Sunray Mid-Continent Oil Company
(Company or Operator)By **R. E. Statton**
Position **District Engineer**
Send Communications regarding well to:Name **C. T. McClanahan**
Address **Box 128, Hobbs, New Mexico**