

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified in to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

| | | | | | |
|---|--|---|----------|---|--|
| NOTICE OF INTENTION TO CHANGE PLANS | | NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL | | NOTICE OF INTENTION TO DRILL DEEPER | |
| NOTICE OF INTENTION TO PLUG WELL | | NOTICE OF INTENTION TO PLUG BACK | | NOTICE OF INTENTION TO SET LINER | |
| NOTICE OF INTENTION TO SQUEEZE | | NOTICE OF INTENTION TO ACIDIZE | | NOTICE OF INTENTION TO SHOOT (Nitro) | |
| NOTICE OF INTENTION TO GUN PERFORATE | | NOTICE OF INTENTION (OTHER) Dual Completion | X | NOTICE OF INTENTION (OTHER) | |

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

(Place)

August 21, 1959

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Sunray Mid-Continent Oil Company

(Company or Operator) D. Hardy Well No. 2 in G (Unit)
SW 1/4 NE 1/4 of Sec. 29, T. 21S, R. 37E, NMPM., Drinkard Pool
 (40-acre Subdivision)
 County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Propose to kill well with oil and pull tubing. Run Gamma Ray neutron logs surface to TD. Set Baker CI bridge plug at 5200'. Perforate 4 holes at 5166' and squeeze cement. Perforate 4 holes at 5140' and squeeze cement. Drill out to 5160' and pressure test casing. Perforate 5150' to 5160'. Acidize with 500 gallons MCA. Swab test. Reacidize if necessary. Kill well with oil. Pull packer and tubing, drill out to PBTD, and set Baker Model "D" production packer at 6500'. Run two strings of 2-3/8" OD tubing, one string with turn down collars. Set one string in packer and set other string at approximately 5150'. Swab in both zones. Potential and take necessary state tests.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

SUNRAY MID-CONTINENT OIL COMPANY

Company or Operator

By.....

Position..... District Engineer

Send Communications regarding well to:

Name..... C. T. McClanahan

Address..... P. O. Box 128, Hobbs, New Mexico