## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Notice by Checking Below

Notice of Intention	NOTICE OF IN FENCION TO	Notice of Intention
to Change Plans	TEMPORARILY ABANDON WELL	to Drill Deeper
Notice of Intention	Notice of Intention	Notice of Intention
to Plug Well	to Plug Back	to Set Liner
Notice of Intention	NOTICE OF INTENTION	Notice of Intention
to Squeeze	TO ACIDIZE	to Shoot (Nitro)
Notice of Intention	NOTICE OF INTENTION	Notice of Intention
to Gun Perforate	(Other)	(Other)

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

Hobbs,	New	Mexi	.00
	(Pla		

**October 30, 1962** (Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Sunray DX 011 Company	STREET	D.	Hardy		Well No	.in
(Company or Operator) <b>SE</b> 1/4 <b>NE</b> 1/4 of Sec. <b>29</b> , T.	218		<sub>R</sub> 37E	NMPM	Wants Abo	(Unit) Pool
(40-acre Subdivision)		, .	** *	· · · · · · · · · · · · · · · · · · ·		

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

- 1. Move in pulling unit. Check possible casing obstruction @ 6600' and PBTD with gauge ring. If obstruction @ 6600' proves to involve casing failure, will submit revised C-102 based on work necessary to repair.
- 2. If casing clear, set cast iron bridge plug @ 7315' and cap with cement (to shut off old Montoya perfs), Test plug for seal. Perforate additional Abc section between 6806 and 7018'.
- 3. Treat old Abo perfs between 7113-7276' with 15,000 gals acid petrofrac and test using two packers for confinement.
- 4. Treat new Abo perfs between 6806-7018: with 15,000 gals NE acid using two packers. Pull packers, run tubing and put back on production.

Approved	By
Approved OIL CONSEBVATION COMMISSION	Position. District Engineer Send Communications regarding well to:
By ////	C. T. McClanahan
Title	Box 128, Hobbs, New Mexico