

| | |
|-------------------|------------|
| NUMBER | RECEIVED |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| TRANSPORTER | DE- SES |
| PRODUCTION OFFICE | |
| OPERATOR | |

(Form C-108)
(Revised 7/1/58)

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be furnished to the Bureau on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

| | | | | | |
|--------------------------------------|--|---|-------------------------------------|-------------------------------------|--|
| NOTICE OF INTENTION TO CHANGE PLANS | | NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL | | NOTICE OF INTENTION TO DRILL DEEPER | |
| NOTICE OF INTENTION TO PLUG WELL | | NOTICE OF INTENTION TO PLUG BACK | <input checked="" type="checkbox"/> | NOTICE OF INTENTION TO SET LINER | |
| NOTICE OF INTENTION TO SQUEEZE | | NOTICE OF INTENTION TO ACIDIZE | | NOTICE OF INTENTION TO SHOOT (Nkro) | |
| NOTICE OF INTENTION TO GUN PERFORATE | | NOTICE OF INTENTION (OTHER) | | NOTICE OF INTENTION (OTHER) | |

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

January 4, 1968
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation **H. T. Mattern (NCT-B)** Well No. **8** in **I**
(Company or Operator) (Unit)
NE 1/4 SE 1/4 of Sec. 30, T. 21-S, R. 37-E, NMPM., Blinbry Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 6568'. Drinkard producing thru open hole 6529 - 6568'. 7" casing set at 6529'. Cemented with 700 sacks. Temp. survey indicated top cement at 1720'.

It is proposed to abandon Drinkard pay and recomplete in Blinbry oil pay as follows:

1. Kill well with lse oil and pull tbg.
2. Set CI BP at 6500' (dump 2 sacks cement on top).
3. Run tbg, displace oil with no bloc mud, pressure test csg & BP w/1000# & pull tbg.
4. Run GB-N log (2" scale: 6500-3000'; 5" scale: 6500-5000' & 4000-3000').
5. Perforate Blinbry from approx 5780' to 5980' in 2' intervals w/4 JHPF. Geologist will determine exact intervals to be perforated.
6. Run 3-1/2" OD tbg w/ret. BP & FB pkr. Treat perforated intervals w/15% NEA followed by a refined oil-nitrogen frac.
7. Swab and test.
8. Kill well w/no bloc mud and pull frac tbg & straddle tools. Run 2-3/8" OD 4.7# EUE j-55 tbg for production string and place well on production.

Approved....., 19.....
Except as follows:

Gulf Oil Corporation
By *[Signature]*

Position **Area Production Manager**
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By *[Signature]*
Title.....

Name **Gulf Oil Corporation**
Address **Box 2167, Hobbs, New Mexico**