

Santa Fe, New Mexico

DUPLICATE

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

The Texas Company

Drawer K, Wink, Texas

V. M. Henderson

Well No.

2-1/2

30

21-3

37-2 Lease

Eunice

Lea

R. 2315, N. M. P. M.

550

Section 30

Well is feet south of the North line and feet west of the East line of

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Mrs. V. M. Henderson

Address 1437 Beattens Bldg. St. Louis, Mo.

If Government land the permittee is

Address Box 2332, Houston, Texas

The Lessee is The Texas Company

Address

Drilling commenced December 5 1936

Drilling was completed December 29, 1936

Name of drilling contractor Gardner Bros.

Address Dallas, Texas

Elevation above sea level at top of casing 5479 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3770 to 3775 No. 4, from to
No. 2, from 3615 to 3620 No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13" OD	40 1/2	8	LW	150'	TP			
9-5/8"	40 1/2	8	Sals	1293'	Guide			
7" OD	24 1/2	10	"	5475'	"			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	13"	157'	160	Halliburton		
	9-5/8"	1293'	700	"		
	7" OD	5460'	275	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Acid	2000 gals	1-1-37	5475-5620	
9-1/2"		Nitroglycerine	200 qts	1-3-37	5725-5820	5820

Results of shooting or chemical treatment Before Acid 50 bbls. per day
After Acid 50 bbls per day
After shot 107 bbls. per day

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 5620 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing January 6 1937 GAS/OIL RATION 4300
The production of the first 24 hours was 107 barrels of fluid of which 100 % was oil; % emulsion; % water; and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

G. G. Stanton, Driller G. T. Hame, Driller
W. H. Hanks, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 15th day of January, 1937
Notary Public.

Wink, Texas January 15, 1937
Name
Position District Superintendent
Representing THE TEXAS COMPANY
Address Drawer K, Wink, Texas

