



AREA 640 ACRES  
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

TEXACO Inc. V. M. Henderson  
(Company or Operator) (Lessee)  
Well No. 8, in SW 1/4 of NW 1/4, of Sec. 30, T. 21-S, R. 37-E, NMPM.  
Penrose Skelly, Paddock, Drinkard Pool, Lea County.  
Well is 660 feet from West line and 1980 feet from North line  
of Section 30. If State Land the Oil and Gas Lease No. is Patented  
Drilling Commenced February 6, 1962 Drilling was Completed March 2, 1962  
Name of Drilling Contractor Cactus Drilling Company  
Address P. O. Box 32, Midland, Texas  
Elevation above sea level at Top of Tubing Head 3510' (D. F.)  
July 1962 The information given is to be kept confidential until

See Attached Sheet OIL SANDS OR ZONES  
No. 1, from to No. 4, from to  
No. 2, from to No. 5, from to  
No. 3, from to No. 6, from to

Drilled with Rotary Tools and no Water Sands tested.  
IMPORTANT WATER SANDS  
Include data on rate of water inflow and elevation to which water rose in hole.  
No. 1, from to feet  
No. 2, from to feet  
No. 3, from to feet  
No. 4, from to feet

CASING RECORD							
SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
11-3/4"	23.72	New	318'	Baker	None	None	Surface
8-5/8"	24.00	New	2991'	Howco	None	None	Intermediate
2-3/8"	4.60	New	6737'	Brown	None	See Attached	Production
2-3/8"	4.60	New	6737'	Brown	None	See Attached	Production
2-3/8"	4.60	New	5320'	Brown	None	See Attached	Production

MUDDING AND CEMENTING RECORD						
SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15"	11-3/4"	329'	300	Howco		
10-5/8"	8-5/8"	3000'	1650	Howco		
7-5/8"	2-3/8"	6744'	* 1320	Howco		
7-5/8"	2-3/8"	6744'	* 1320	Howco		
7-5/8"	2-3/8"	5329'	* 1320	Howco	* Three Strings cemented with 1320 sx.	

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

See attached  
Result of Production Stimulation See Attached

Depth Cleaned Out 6745'  
PBD 6733'

# RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

## TOOLS USED

Rotary tools were used from 0 feet to 6745 feet, and from feet to feet.  
Cable tools were used from feet to feet, and from feet to feet.

## PRODUCTION

Put to Producing March 16, 1962

OIL WELL: The production during the first 24 hours was 194 barrels of liquid of which 34 % was  
was oil; % was emulsion; 66 % water; and % was sediment. A.P.I.  
Gravity 37

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of  
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

### Southeastern New Mexico

T. Anhy. 1200'  
T. Salt. 1370'  
B. Salt. 2475'  
T. Yates. 2610'  
T. 7 Rivers.  
T. Queen. 3385'  
T. Grayburg. 3648'  
T. San Andres. 3951'  
T. Glorieta. 5115'  
T. Blinberry. 5567'  
T. Tubbs. 6250'  
T. Drinkard. 6622'  
T. Penn.  
T. Miss.

T. Devonian.  
T. Silurian.  
T. Montoya.  
T. Simpson.  
T. McKee.  
T. Ellenburger.  
T. Gr. Wash.  
T. Granite.  
T.  
T.  
T.  
T.  
T.

### Northwestern New Mexico

T. Ojo Alamo.  
T. Kirtland-Fruitland.  
T. Farmington.  
T. Pictured Cliffs.  
T. Menefee.  
T. Point Lookout.  
T. Mancos.  
T. Dakota.  
T. Morrison.  
T. Penn.  
T.  
T.  
T.  
T.

## FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	260	260	Caliche				Deviation Record
260	1200	940	Redbed			Depth	Degrees Off
1200	1370	170	Redbed and Anhy			800'	3/4
1370	2475	1105	Top of Salt			1100'	1
2475	2575	100	Anhy and Salt			1450'	1-1/4
2575	3385	810	Anhy and Gyp			1760'	1/4
3385	4357	972	Anhy and Lime			2579'	2
4357	5680	1323	Lime and Sand			2881'	1-1/4
5680	6220	540	Lime			3400'	1-3/4
6220	6745	525	Lime and Sand			3777'	1
Total Depth	6745					4440'	1-1/4
PBTD	6733					4730'	1-1/4
						5448'	3/4
						5914'	1-1/4
						6262'	1-1/2
						6450'	1-1/2
						6745'	1-1/2

All Measurements from Rotary  
Table or 9' above ground Level  
Estimate No. 5755  
5 - NOCC  
1 - Division  
1 - Field  
1 - File

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator TEXACO Inc. H. N. Wade March 20, 1962  
Address P. O. Box 728, Hobbs, New Mexico  
Name Assistant District Superintendent