

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-101
Effective 1-1-65

5a. Indicate Type of

State ☐

XX

5. State Oil & Gas

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REFIN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Water Injection Well	7. Unit Agreement <input type="checkbox"/>
2. Name of Operator Gulf Oil Corporation	8. Central Drinkard Unit
3. Address of Operator Box 670, Hobbs, New Mexico 88240	9. Well No. 151
4. Location of Well UNIT LETTER I 1980 FEET FROM THE South LINE AND 330 FEET FROM THE East LINE, SECTION 31 TOWNSHIP 21-S RANGE 37-E NMPM.	10. Field and Pool, Drinkard
15. Elevation (Show whether DF, RT, GR, etc.) 3480' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

Repaired communications

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting work) SEE RULE 1103.

6629' PB.

Pulled injection equipment. Squeezed Drinkard perforations 6543' to 6547' with 200 sacks of Class C cement. WOC 18 hours. Tested previously squeezed Tubb perforations 6135' to 6310' with 500#, leaked off to 0# in 2-1/2 minutes. Re-squeezed perforations 6135' to 6310' with 100 sacks of Class C cement. WOC 18 hours. Cleaned out to 6629' and tested Tubb perforations 6135' to 6310' with 1500#, 30 minutes, OK. Tested squeezed Drinkard perforations 6543' to 6547' with 500# compression. Water is now being injected thru Drinkard perforations 6560' to 6618'.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED D. F. Berlin TITLE Area Engineer DATE December 9,

APPROVED BY Orly Signed Es TITLE Area Section DATE DEC 10

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

FEB 9 1975

LA CONSERVATION COMMISSION
BUREAU OF LAND