

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report of Plug Back	X

April 12, 1948

Date

Hobbs, New Mexico

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation

McCormack

Well No. 12 in the

Company or Operator

Lease

NW NE

of Sec. 32

T. 21S

R. 37E

N. M. P. M.,

Drinkard

Field,

Lea

County.

The dates of this work were as follows: April 4, 1948 to April 11, 1948.

Notice of intention to do the work was (~~was~~) submitted on Form C-102 on April 8, 1948and approval of the proposed plan was (~~was~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

After running and cementing 7" csg the plug was drilled out to 7400', which is 19' above previous total depth. Perforated 7" csg from 7305' to 7320', 7335' to 7360' and from 7390' to 7400' w/6 - 1/2 HPF by McCullough and acidized w/1000 gals by Dowell. Well not productive. Ran and set 7" 17-22# type DSL Lane Wells Bridging plug at 6700'. Dumped 2 sacks Calseal and 4 sacks cement on top of plug by HOWCO. Top of cement at 6666'. Perforated 7" csg from 6515' to 6620' w/six 15/32" HPF by Lane Wells. Acidized with 1000 gals by Chemical Process. Well flowed 255 bbls oil (.5% BS&W) in 24 hrs through 3/4" Choke.

Witnessed by	G. Stach	Gulf Oil Corporation	Drilling Foreman
	Name	Company	Title

Subscribed and sworn before me this

12th day of April 1948

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name E. J. GallagherPosition District Sup't.Representing Gulf Oil Corporation

Company or Operator

My commission expires 10-24-49

Address Box 1667, Hobbs, New Mexico

Remarks:

APPROVED  
Date: April 14, 1948

Name  
Title

# THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH

THEORY OF THE EARTH