

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

Nov. 16, 1948

Place


Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as \_\_\_\_\_  
**Skelly Oil Co.** State "NM" Well No. 4 in NW/4 NW/4

Company or Operator Lease  
of Sec. 32, T 21S, R 37E, N. M., P. M., Drinkard Field, Lea County.  
N



AREA 640 ACRES

LOCATE WELL CORRECTLY  
top to total depth.

The well is 660 feet UNK (S.) of the North line and 990 feet  
(E.) UNK of the West Line line of Sec. 32

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. B-1327 Assignment No. \_\_\_\_\_

If patented land the owner is \_\_\_\_\_

Address \_\_\_\_\_

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is Skelly Oil Co.

Address Tulsa, Okla.

We propose to drill well with drilling equipment as follows: Rotary tools from

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: \_\_\_\_\_

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
17-1/4"	13-3/8	44.5	New	160'	Cemented	150
11"	9-5/8"	36	New	2750'	Cemented	1000
7-3/8"	5-1/2"	17	New	6600'	Cemented	300

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 6500 feet.

Additional information: Halliburton process will be used in cementing all casing.

NOV 19 1948

Approved \_\_\_\_\_, 19\_\_\_\_

except as follows:

Sincerely yours,

Skelly Oil Company

Company or Operator

By \_\_\_\_\_

Position Dist. Supt.

Send communications regarding well to

Name Skelly Oil Co.

Address Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By \_\_\_\_\_

Title \_\_\_\_\_